





1. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.
2. FOR BEST RESULTS, BE SURE PANEL MOUNTS ARE MOUNTED FLAT TO SURFACE.
3. ALIGNMENT BRACKETS ARE AVAILABLE FOR THE SPACING SHOWN. (OPTIONAL)
4. USE SPACER BRACKETS TO SPACE OFF UNEVEN WALLS (PROVIDED).
5. PANEL MOUNTS CAN BE ROTATED CLOCKWISE 90°.
6. ROUTE WALL CABLES (POWER AND DISPLAY PORT) AFTER ALL MOUNTS ARE INSTALLED.
7. DISPLAY PORT IN COMES FROM THE SOURCE OR OUTPUT OF PREVIOUS PANEL IN ARRAY. 48V IN COMES FROM THE POWER SUPPLY OR OUTPUT OF PREVIOUS PANEL IN ARRAY.
8. AT A MINIMUM MOUNT TO STRUCTURE NEAR CORNERS.
9. KEEP CABLES CLEAR OF PANEL GUIDE POSTS AND TOPS OF SNAP CATCHES.

NOTES: UNLESS OTHERWISE SPECIFIED.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS (INCHES)		ENGR BY EJS	02MAY12	PLANAR PLANAR SYSTEMS, INC. 1195 NW COMPTON DRIVE BEAVERTON, OR 97006 USA
TOLERANCES:		DRAWN BY EJS	02MAY12	
X= ±1	XX= ±.25	CHECKED BY		TITLE MOSAIC AD22 MOUNT BRACKET LAYOUT STANDARD 2mm SPACING
.X= ±.5	∠= ±1°	USED ON		
DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994		MATERIAL		SIZE D
THIRD ANGLE PROJECTION		FINISH		
DRAWING NO.		PART NO.		REV 04
SCALE		1:4	DO NOT SCALE	SHEET 2 OF 2

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.