

## Planar UltraRes UR8451-LX-ER0

4K LCD Display

The Planar® UltraRes<sup>™</sup> UR8451-LX-ERO is an 84" Ultra HD (3840 x 2160) professional LCD display with best-in-class image and color quality for native 4K and upscaled content. This 350 nit 84" display supports multi-source viewing, 4K @ 60Hz, and HDCP 2.2 compliance. Planar UltraRes Series displays offer superior performance with exceptional 4K clarity and advanced processing ideal for applications ranging from collaborative meeting spaces to high impact digital signage. Planar UR8451-LX-ERO combines Planar® ERO<sup>™</sup>(Extended Ruggedness and Optics<sup>™</sup>) technology with Corning® Gorilla® Glass, creating a highly durable 4K display.



SPECIFICATION	DETAIL
Product Name	UR8451-LX-ERO
Display Resolution	Ultra HD (3840 x 2160)
Screen Size	84 in. (diagonal)
Aspect Ratio	16:9
Display Active Area	73.2" (1860mm) x 41.2" (1046mm)
Cabinet Dimensions (W x H x D)	◆75.5" x 43.7" x 3.6" (1919mm x 1111mm x 93mm)
Dimensions, including wall mount	75.5" x 43.7" x 3.6" (1919mm x 1111mm x 93mm)
Bezel Width	1.15" (29.1mm) left/right; 1.26" (32.1mm) top/bottom
Protective Glass	ERO optically-bonded glass technology featuring Corning Gorilla Glass, 2mm AG
Brightness (typ)	350 nits
Response Time (typ)	5 ms
Frame Rate	120Hz
Contrast Ratio (typ)	1600:1
Viewing Angle (typ)	178°
Color Gamut	72% NTSC
Display Color	>1 billion colors. Full 10 bit data path
Modes	1x 3840x2160 @ 24/25/30/60Hz; 4x 1920x1080 @ 24/25/30/50/60Hz; 4x 960x2160 @ 60Hz; 2x 1920x2160 @ 60Hz; 480p, 576p, 720p @ 50/60 Hz; 1080p @ 24/25/30/50/60Hz; 1080i @ 50/60 Hz

Weight225 lb (102 kg)Weight (Shipping)TBDBacklightLEDLine Voltage100-240V; 50/60HzPower Consumption (typ)360WOperating Temperature0° to +35°C (32° to 95°F) at up to 1500m, 0° to +30°C (32° to 86°F) a 3000mHumidity20 - 85% RH (non-condensing)ApprovalsFCC Class A, CE, cTUVusExternal ConnectionsDisplayPort 1.2 x 1, HDMI® 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2, OPS USB 2.0 x 2, OPS USB 3.0 X 1Audio OutputPC Line Out, S/PDIFMulti-Source ViewsPiP, Dual, Triple, QuadDisplay ControlIR, RS-232, LAN, Keypad, Mobile appSpeakers10W x 2 built-inOrientationLandscapeMountingPlanar Profile Mounting System or VESA: 600 x 400 mmFanlessYesHD format4K UHD 2160pDisplay TechnologyEdge-lit LED LCDOptions / FeaturesMediaPlex Plus Processing, Scheduling, Presets, Redundant power compliant.Warranty3 years Advance Exchange	
BacklightLEDLine Voltage100-240V; 50/60HzPower Consumption (typ)360WOperating Temperature0° to +35°C (32° to 95°F) at up to 1500m, 0° to +30°C (32° to 86°F) a 3000mHumidity20 - 85% RH (non-condensing)ApprovalsFCC Class A, CE, cTUVusExternal ConnectionsDisplayPort 1.2 x 1, HDMI® 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2, OPS USB 2.0 x 2, OPS USB 3.0 X 1Audio OutputPC Line Out, S/PDIFMulti-Source ViewsPiP, Dual, Triple, QuadDisplay ControlIR, RS-232, LAN, Keypad, Mobile appSpeakers10W x 2 built-inOrientationLandscapeMountingPlanar Profile Mounting System of VESA+600 x 400 mmFanlessYesHD format4K UHD 2160pDisplay TechnologyEdge-lit LED LCDOptions / FeaturesMediaPlex Plus Processing, Scheduling, Presets, Redundant power compliant	
Line Voltage100-240V; 50/60HzPower Consumption (typ)360WOperating Temperature0° to +35°C (32° to 95°F) at up to 1500m, 0° to +30°C (32° to 86°F) a 3000mHumidity20 - 85% RH (non-condensing)ApprovalsFCC Class A, CE, cTUVusExternal ConnectionsDisplayPort 1.2 x 1, HDM(® 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2, OPS USB 2.0 x 2, OPS USB 3.0 X 1Audio OutputPC Line Out, S/PDIFMulti-Source ViewsPiP, Dual, Triple, QuadDisplay ControlIR, RS-232, LAN, Keypad, Mobile appSpeakers10W x 2 built-inOrientationLandscapeMountingPlanar Profile Mounting System of VESA: 600 x 400 mmFanlessYesHD format4K UHD 2160pDisplay TechnologyEdge-lit LED LCDOptions / FeaturesMediaPlex Plus Processing, Scheduling, Presets, Redundant power compliant	
Power Consumption (typ)360WOperating Temperature0° to +35°C (32° to 95°F) at up to 1500m, 0° to +30°C (32° to 86°F) at 3000mHumidity20 - 85% RH (non-condensing)ApprovalsFCC Class A, CE, cTUVusExternal ConnectionsDisplayPort 1.2 x 1, HDMI® 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2, OPS USB 2.0 x 2, OPS USB 3.0 X 1Audio OutputPC Line Out, S/PDIFMulti-Source ViewsPiP, Dual, Triple, QuadDisplay ControlIR, RS-232, LAN, Keypad, Mobile appSpeakers10W x 2 built-inOrientationLandscapeMountingPlanar Profile Mounting System or VESA: 600 x 400 mmFanlessYesHD format4K UHD 2160pDisplay TechnologyEdge-lit LED LCDOptions / FeaturesMediaPlex Plus Processing, Scheduling, Presets, Redundant power compliant	
Operating Temperature0° to +35°C (32° to 95°F) at up to 1500m, 0° to +30°C (32° to 86°F) at 3000mHumidity20 - 85% RH (non-condensing)ApprovalsFCC Class A, CE, cTUVusExternal ConnectionsDisplayPort 1.2 x 1, HDMI® 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2, OPS USB 3.0 X 1Audio OutputPC Line Out, S/PDIFMulti-Source ViewsPiP, Dual, Triple, QuadDisplay ControlIR, RS-232, LAN, Keypad, Mobile appSpeakers10W x 2 built-inOrientationLandscapeMountingPlanar Profile Mounting System or VESA-600 x 400 mmFanlessYesHD format4K UHD 2160pDisplay TechnologyEdge-lit LED LCDOptions / FeaturesMediaPlex Plus Processing, Scheduling, Presets, Redundant power compliant	
3000mHumidity20 - 85% RH (non-condensing)ApprovalsFCC Class A, CE, cTUVusExternal ConnectionsDisplayPort 1.2 x 1, HDMI® 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2, OPS USB 2.0 x 2, OPS USB 3.0 X 1Audio OutputPC Line Out, S/PDIFMulti-Source ViewsPiP, Dual, Triple, QuadDisplay ControlIR, RS-232, LAN, Keypad, Mobile appSpeakers10W x 2 built-inOrientationLandscapeMountingPlanar Profile Mounting System of VESA: 600 x 400 mmFanlessYesHD format4K UHD 2160pDisplay TechnologyEdge-lit LED LCDOptions / FeaturesMediaPlex Plus Processing, Scheduling, Presets, Redundant power compliant.	
ApprovalsFCC Class A, CE, cTUVusExternal ConnectionsDisplayPort 1.2 x 1, HDMI® 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2, OPS USB 2.0 x 2, OPS USB 3.0 X 1Audio OutputPC Line Out, S/PDIFMulti-Source ViewsPiP, Dual, Triple, QuadDisplay ControlIR, RS-232, LAN, Keypad, Mobile appSpeakers10W x 2 built-inOrientationLandscapeMountingPlanar Profile Mounting System or VES/4:600 x 400 mmFanlessYesHD format4K UHD 2160pDisplay TechnologyEdge-lit LED LCDOptions / FeaturesMediaPlex Plus Processing, Scheduling, Presets, Redundant power compliant	at up to
External ConnectionsDisplayPort 1.2 x 1, HDMI® 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2, OPS USB 2.0 x 2, OPS USB 3.0 X 1Audio OutputPC Line Out, S/PDIFMulti-Source ViewsPiP, Dual, Triple, QuadDisplay ControlIR, RS-232, LAN, Keypad, Mobile appSpeakers10W x 2 built-inOrientationLandscapeMountingPlanar Profile Mounting System or VESA: 600 x 400 mmFanlessYesHD format4K UHD 2160pDisplay TechnologyEdge-lit LED LCDOptions / FeaturesMediaPlex Plus Processing, Scheduling, Presets, Redundant power compliant	
USB 2.0 x 2, OPS USB 3.0 X 1Audio OutputPC Line Out, S/PDIFMulti-Source ViewsPiP, Dual, Triple, QuadDisplay ControlIR, RS-232, LAN, Keypad, Mobile appSpeakers10W x 2 built-inOrientationLandscapeMountingPlanar Profile Mounting System or VESA: 600 x 400 mmFanlessYesHD format4K UHD 2160pDisplay TechnologyEdge-lit LED LCDOptions / FeaturesMediaPlex Plus Processing, Scheduling, Presets, Redundant power scompliant	
Multi-Source ViewsPiP, Dual, Triple, QuadDisplay ControlIR, RS-232, LAN, Keypad, Mobile appSpeakers10W x 2 built-inOrientationLandscapeMountingPlanar Profile Mounting System or VESA: 600 x 400 mmFanlessYesHD format4K UHD 2160pDisplay TechnologyEdge-lit LED LCDOptions / FeaturesMediaPlex Plus Processing, Scheduling, Presets, Redundant power scompliant	x 1, OPS
Display Control IR, RS-232, LAN, Keypad, Mobile app   Speakers 10W x 2 built-in   Orientation Landscape   Mounting Planar Profile Mounting System or VESA: 600 x 400 mm   Fanless Yes   HD format 4K UHD 2160p   Display Technology Edge-lit LED LCD   Options / Features MediaPlex Plus Processing, Scheduling, Presets, Redundant power scompliant	
Speakers 10W x 2 built-in   Orientation Landscape   Mounting Planar Profile Mounting System or VESA: 600 x 400 mm   Fanless Yes   HD format 4K UHD 2160p   Display Technology Edge-lit LED LCD   Options / Features MediaPlex Plus Processing, Scheduling, Presets, Redundant power scompliant	
OrientationLandscapeMountingPlanar Profile Mounting System or VESA: 600 x 400 mmFanlessYesHD format4K UHD 2160pDisplay TechnologyEdge-lit LED LCDOptions / FeaturesMediaPlex Plus Processing, Scheduling, Presets, Redundant power scompliant	
Mounting Planar Profile Mounting System or VESA: 600 x 400 mm   Fanless Yes   HD format 4K UHD 2160p   Display Technology Edge-lit LED LCD   Options / Features MediaPlex Plus Processing, Scheduling, Presets, Redundant power scompliant	
Fanless Yes   HD format 4K UHD 2160p   Display Technology Edge-lit LED LCD   Options / Features MediaPlex Plus Processing, Scheduling, Presets, Redundant power scompliant	
HD format 4K UHD 2160p   Display Technology Edge-lit LED LCD   Options / Features MediaPlex Plus Processing, Scheduling, Presets, Redundant power scompliant	
Display Technology Edge-lit LED LCD   Options / Features MediaPlex Plus Processing, Scheduling, Presets, Redundant power scompliant	
Options / Features   MediaPlex Plus Processing, Scheduling, Presets, Redundant power scompliant	
compliant	
Warranty   3 years Advance Exchange	supply, TAA
Planar Part Number 997-8087-00	
UPC 8 10689 00256 7	

For more information, please visit www.planar.com

Specifications are subject to change without notice. Specification Report Date: 10/21/2016

© Copyright 2016 Planar Systems, Inc. All rights reserved

Planar utilizes HDMI® standards in this product.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.