



Planar RA4980

Narrow Bezel LCD Video Wall

The Planar® RA Series LCD displays deliver a simplified video wall solution that supports the demanding requirements of 24x7 mission critical applications and high ambient light environments. The 49" narrow bezel LCD video wall displays feature a wide range of features which enable simplified and versatile video wall installation.



SPECIFICATION	DETAIL
Product Name	RA4980
Planar Part Number	997-7951-00
Viewable Size	49" diagonal
Display Active Area	42.3" x 23.8" (1073.8mm x 604.0mm)
Aspect Ratio	16:9
Display Resolution	1920 x 1080, full HD
Brightness (Typical)	700 cd/m ²
Contrast Ratio (typ)	1300:1
Response Time (typ)	8 ms
Viewing Angle (typ)	178°
External Connections	HDMI x 2, DVI in/out, DisplayPort in/out, VGA, Component, Composite
Audio Input	Phone jack and L/R RCA jack
Audio Output	Phone jack, external speaker connector
Display Control	IR, RS232, LAN, Keypad
Line Voltage	100-240V: 50/60Hz
Power Consumption (typ)	120W
Product Approvals	FCC Class B, cTUVus, CE
Cabinet Dimensions (W x H x D)	43.0" x 24.5" x 2.2" (1092.3mm x 622.5mm x 56.8mm)
Tiled Bezel Width	12.6mm
Bezel Width	6.3 mm

VESA Compatible/Location	VESA 400 x 400
Display Weight	42 lb (19 kg)
Weight (Shipping)	56 lb (25 kg)
Display Type	Commercial-grade LCD with LED backlight
Operating Temperature	0-40°C (32 -104°F)
Operating Relative Humidity	20-80%
Palette	1.073B colors (10 bit)
Color Gamut	72% NTSC
Pixel Pitch	0.55926mm x 0.55926mm
Orientation	Landscape/Portrait
Speakers	10W x 2 built-in
UPC	8 10689 00240 6
Features	OPS slot, on/off scheduling, source failover, up to 10x10 video wall scaling, carrying handles
In the Box	RA4980 display, AC Power Cord (US), DisplayPort cable, Remote control, IR Receiver, IR loop cable, RS-232 cable, RS-232 loop cable, alignment brackets, Quick Start Guide
Service and Support/Warranty	3-year Advance Exchange

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 1/18/2018

© Copyright 2018 Planar Systems, Inc. All rights reserved