

PLL2450MW

24" LCD Monitor

The Planar® PLL2450MW 24" Full HD LCD desktop monitor features integrated TrueMediaTM speakers and VGA and HDMI® video inputs. With its small footprint, it can be mounted on a multimonitor stand for home, office or healthcare applications. It offers wide viewing angles and excellent color balance. Blue light reduction pre-sets help lower eye fatigue and maintain visual comfort. Its 100mm VESA compatibility pairs well with Planar accessories like Dual or Triple Monitor Stands.



SPECIFICATION	DETAIL
Product Name	PLL2450MW
Planar Part Number	997-9045-00
Viewable Size	23.6" diagonal (20.52" horizontal x 11.54" vertical)
Aspect Ratio	16:9
Contrast Ratio (typ)	3000:1
Viewing Angle (typ)	178° Horizontal and 178° Vertical (Specified at CR>10:1)
Response Time (typ)	12.5 ms (GTG)
Brightness (Typical)	250 cd/m²
Display Type	Edge-Lit LED LCD
Display Resolution	1920 x 1080, full HD
Tilt Range	-5° to +20°
Palette	16.7 million colors
Pixel Pitch	0.2715 mm

Dimensions (W x H x D) Dimensions without 21.6" x 16.0" x 6.7" (547.6 mm x 405.5 mm x 170.4 mm) Dimensions without 21.6" x 12.8" x 1.6" (547.6 mm x 324.3 mm x 40.9 mm) Stand Panel Depth 1.6" (40.9 mm) Display Weight 6.9 lb (3.12 kg), 6.4 lb (2.87 kg) without base & stand Shipping weight 8.5 lb (3.85 kg) Video Inputs HDMI®, VGA HDCP Yes External Connections HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating 5° to +40°C (41° to 104°F) Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes In the Box PLL2450MW 24" LED LCD Monitor, C5 Connector Power Cord, HDMI		
D) Dimensions without Stand Panel Depth 1.6" (40.9 mm) Display Weight 6.9 lb (3.12 kg), 6.4 lb (2.87 kg) without base & stand Shipping weight 8.5 lb (3.85 kg) Video Inputs HDMI 9-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes	Refresh Rate	55-76Hz (60Hz recommended)
Panel Depth 1.6" (40.9 mm) Display Weight 6.9 lb (3.12 kg), 6.4 lb (2.87 kg) without base & stand Shipping weight 8.5 lb (3.85 kg) Video Inputs HDMI®, VGA HDCP Yes External Connections HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/CUL, ROHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes	·	21.6" x 16.0" x 6.7" (547.6 mm x 405.5 mm x 170.4 mm)
Display Weight 6.9 lb (3.12 kg), 6.4 lb (2.87 kg) without base & stand Shipping weight 8.5 lb (3.85 kg) Video Inputs HDMI ⊕, VGA HDCP Yes External Connections HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes		21.6" x 12.8" x 1.6" (547.6 mm x 324.3 mm x 40.9 mm)
Shipping weight Video Inputs HDMI®, VGA HDCP Yes External Connections HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes	Panel Depth	1.6" (40.9 mm)
Video Inputs HDMI®, VGA HDCP Yes External Connections HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) 18.5 Watts typical (<0.5W standby)	Display Weight	6.9 lb (3.12 kg), 6.4 lb (2.87 kg) without base & stand
HDCP Yes External Connections HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes	Shipping weight	8.5 lb (3.85 kg)
External Connections HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes	Video Inputs	HDMI®, VGA
Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) 18.5 Watts typical (<0.5W standby) Power Requirements AC 100/240 VAC Operating 5° to +40°C (41° to 104°F) Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, ROHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes	HDCP	Yes
Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) 18.5 Watts typical (<0.5W standby) Power Requirements AC 100/240 VAC Operating Temperature 5° to +40°C (41° to 104°F) Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, ROHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes	External Connections	
Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes	Audio Output	Integrated TrueMedia™ speakers, 1W/channel
Power Consumption (max) 18.5 Watts typical (<0.5W standby) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes	Compatibility	PC and Mac® (adapter may be required for Mac)
Power Requirements AC 100/240 VAC Operating Temperature 5° to +40°C (41° to 104°F) Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes	Power Supply	Internal
Operating Temperature 5° to +40°C (41° to 104°F) Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes	·	18.5 Watts typical (<0.5W standby)
Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes	Power Requirements	AC 100/240 VAC
Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes		5° to +40°C (41° to 104°F)
Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes	Humidity	10 - 90% RH (non-condensing)
Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes	Mount	Built-in 100 mm VESA, back
Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi- language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes	Product Approvals	FCC-B, UL/cUL, RoHS
(US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes	Recommended Usage	Up to 16 hours per day
language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes	Service and Support	(US only). Please see the warranty document for more details and for
Flicker Free Yes	Options / Features	
	Blue Light Reduction	Yes
In the Box PLL2450MW 24" LED LCD Monitor, C5 Connector Power Cord, HDMI	Flicker Free	Yes
	In the Box	PLL2450MW 24" LED LCD Monitor, C5 Connector Power Cord, HDMI

	Cable, User's Guide
UPC	8 10689 00410 3
HDMI®	Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 5/18/2024

© Copyright 2024 Planar Systems, Inc. All rights reserved