

PLL2450MW

24" LCD Monitor

The Planar® PLL2450MW 24" Full HD LCD desktop monitor features integrated TrueMediaTM speakers and VGA and HDMI® video inputs. With its small footprint, it can be mounted on a multimonitor stand for home, office or healthcare applications. It offers wide viewing angles and excellent color balance. Blue light reduction pre-sets help lower eye fatigue and maintain visual comfort. Its 100mm VESA compatibility pairs well with Planar accessories like Dual or Triple Monitor Stands.



| SPECIFICATION | DETAIL |
|----------------------|--|
| Product Name | PLL2450MW |
| Planar Part Number | 997-9045-00 |
| Viewable Size | 23.6" diagonal (20.52" horizontal x 11.54" vertical) |
| Aspect Ratio | 16:9 |
| Contrast Ratio (typ) | 3000:1 |
| Viewing Angle (typ) | 178° Horizontal and 178° Vertical (Specified at CR>10:1) |
| Response Time (typ) | 12.5 ms (GTG) |
| Brightness (Typical) | 250 cd/m² |
| Display Type | Edge-Lit LED LCD |
| Display Resolution | 1920 x 1080, full HD |
| Tilt Range | -5° to +20° |
| Palette | 16.7 million colors |
| Pixel Pitch | 0.2715 mm |

| Dimensions (W x H x D) Dimensions without 21.6" x 16.0" x 6.7" (547.6 mm x 405.5 mm x 170.4 mm) Dimensions without 21.6" x 12.8" x 1.6" (547.6 mm x 324.3 mm x 40.9 mm) Stand Panel Depth 1.6" (40.9 mm) Display Weight 6.9 lb (3.12 kg), 6.4 lb (2.87 kg) without base & stand Shipping weight 8.5 lb (3.85 kg) Video Inputs HDMI®, VGA HDCP Yes External Connections HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating 5° to +40°C (41° to 104°F) Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes In the Box PLL2450MW 24" LED LCD Monitor, C5 Connector Power Cord, HDMI | | |
|--|----------------------|--|
| D) Dimensions without Stand Panel Depth 1.6" (40.9 mm) Display Weight 6.9 lb (3.12 kg), 6.4 lb (2.87 kg) without base & stand Shipping weight 8.5 lb (3.85 kg) Video Inputs HDMI 9-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes | Refresh Rate | 55-76Hz (60Hz recommended) |
| Panel Depth 1.6" (40.9 mm) Display Weight 6.9 lb (3.12 kg), 6.4 lb (2.87 kg) without base & stand Shipping weight 8.5 lb (3.85 kg) Video Inputs HDMI®, VGA HDCP Yes External Connections HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/CUL, ROHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes | · | 21.6" x 16.0" x 6.7" (547.6 mm x 405.5 mm x 170.4 mm) |
| Display Weight 6.9 lb (3.12 kg), 6.4 lb (2.87 kg) without base & stand Shipping weight 8.5 lb (3.85 kg) Video Inputs HDMI ⊕, VGA HDCP Yes External Connections HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes | | 21.6" x 12.8" x 1.6" (547.6 mm x 324.3 mm x 40.9 mm) |
| Shipping weight Video Inputs HDMI®, VGA HDCP Yes External Connections HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes | Panel Depth | 1.6" (40.9 mm) |
| Video Inputs HDMI®, VGA HDCP Yes External Connections HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) 18.5 Watts typical (<0.5W standby) | Display Weight | 6.9 lb (3.12 kg), 6.4 lb (2.87 kg) without base & stand |
| HDCP Yes External Connections HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes | Shipping weight | 8.5 lb (3.85 kg) |
| External Connections HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes | Video Inputs | HDMI®, VGA |
| Audio Output Integrated TrueMedia™ speakers, 1W/channel Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) 18.5 Watts typical (<0.5W standby) Power Requirements AC 100/240 VAC Operating 5° to +40°C (41° to 104°F) Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, ROHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes | HDCP | Yes |
| Compatibility PC and Mac® (adapter may be required for Mac) Power Supply Internal Power Consumption (max) 18.5 Watts typical (<0.5W standby) Power Requirements AC 100/240 VAC Operating Temperature 5° to +40°C (41° to 104°F) Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, ROHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes | External Connections | |
| Power Supply Internal Power Consumption (max) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes | Audio Output | Integrated TrueMedia™ speakers, 1W/channel |
| Power Consumption (max) 18.5 Watts typical (<0.5W standby) Power Requirements AC 100/240 VAC Operating Temperature Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes | Compatibility | PC and Mac® (adapter may be required for Mac) |
| Power Requirements AC 100/240 VAC Operating Temperature 5° to +40°C (41° to 104°F) Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes | Power Supply | Internal |
| Operating Temperature 5° to +40°C (41° to 104°F) Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes | · | 18.5 Watts typical (<0.5W standby) |
| Humidity 10 - 90% RH (non-condensing) Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes | Power Requirements | AC 100/240 VAC |
| Mount Built-in 100 mm VESA, back Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes | | 5° to +40°C (41° to 104°F) |
| Product Approvals FCC-B, UL/cUL, RoHS Recommended Usage Up to 16 hours per day 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes | Humidity | 10 - 90% RH (non-condensing) |
| Recommended Usage Up to 16 hours per day Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes | Mount | Built-in 100 mm VESA, back |
| Service and Support 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi- language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes | Product Approvals | FCC-B, UL/cUL, RoHS |
| (US only). Please see the warranty document for more details and for replacement procedures outside the US. Options / Features Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes | Recommended Usage | Up to 16 hours per day |
| language display, On screen display (OSD), Kensington® Security Slot Blue Light Reduction Yes Flicker Free Yes | Service and Support | (US only). Please see the warranty document for more details and for |
| Flicker Free Yes | Options / Features | |
| | Blue Light Reduction | Yes |
| In the Box PLL2450MW 24" LED LCD Monitor, C5 Connector Power Cord, HDMI | Flicker Free | Yes |
| | In the Box | PLL2450MW 24" LED LCD Monitor, C5 Connector Power Cord, HDMI |

| | Cable, User's Guide |
|-------|---|
| UPC | 8 10689 00410 3 |
| HDMI® | Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. |

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 5/19/2024

© Copyright 2024 Planar Systems, Inc. All rights reserved