



# Planar PXN2710Q

27" LCD Monitor

The Planar® PXN2710Q is a 27" Quad HD IPS LED LCD monitor that features an ultra-thin bezel design, ergonomic design, wide viewing angles, numerous digital inputs and integrated TrueMedia™ speakers. The Planar PXN2710Q suits nicely into education, home, office or healthcare applications.



SPECIFICATION	DETAIL
Product Name	PXN2710Q
Planar Part Number	998-2123-00
Viewable Size	27" diagonal (23.53" x 13.21")
Aspect Ratio	16:9
Contrast Ratio (typ)	1000:1
Viewing Angle (typ)	178° Horizontal and Vertical
Response Time (typ)	6 ms (GTG)
Brightness (Typical)	300 cd/m <sup>2</sup>
Display Type	IPS LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	2560 x 1440 WQHD
Tilt Range	-5° to +20°
Palette	16.7 million colors
Pixel Pitch	0.2331 mm
Refresh Rate	48 to 75Hz (60 Hz recommended)
Dimensions (W x H x D)	24.2" x 20.5" x 9.1" (612.84 mm x 519.39 mm x 229.63 mm)

D)	
<b>Dimensions without Stand</b>	24.2" x 14.5" x 2.1" (612.84 mm x 367.46 mm x 52.3 mm)
<b>Panel Depth</b>	2.1" (52.3 mm)
<b>Display Weight</b>	13.1 lb/5.93 kg (9.4 lb/ 4.25 kg without stand)
<b>Shipping weight</b>	16.32lb (7.4 kg)
<b>Video Inputs</b>	HDMI® x 2, DisplayPort
<b>HDCP</b>	Yes
<b>Audio Output</b>	Integrated 2W/channel stereo speakers, headphone jack
<b>External Connections</b>	DisplayPort 20-pin, HDMI 19-pin, 3.5mm headphone out
<b>Compatibility</b>	PC and Mac® (adapter may be required for Mac)
<b>Power Supply</b>	Internal
<b>Power Consumption (max)</b>	35W Typical (<0.5W standby)
<b>Power Requirements</b>	AC 100/240 VAC
<b>Operating Temperature</b>	0° to +40°C (32° to 104°F)
<b>Humidity</b>	10 - 85% RH (non-condensing)
<b>Mount</b>	Built-in 100 mm VESA, back
<b>Product Approvals</b>	cTUVus, CE , FCC-B, RoHS
<b>Recommended Usage</b>	Up to 16 hours per day
<b>Service and Support</b>	3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US.
<b>Options / Features</b>	IPS panel, Wide color consistent viewing angle, Discreet branding, Height adjustment: 4.3" (120cmm), Swivel range 60° (30° left, 30° right), Pivot 90°, Anti-glare coating ,Multi-language display, On screen display (OSD), Kensington® Security Slot
<b>Blue Light Reduction</b>	Yes
<b>Flicker Free</b>	Yes
<b>In the Box</b>	PXN2710Q 27" LED LCD Monitor, Power Cord, HDMI Cable, DisplayPort Cable, User's Guide

<b>UPC</b>	8 10689 00802 6
<b>HDMI®</b>	Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 5/15/2024*

*© Copyright 2024 Planar Systems, Inc. All rights reserved*