



# Planar CarbonLight CLI Flex 1.3

## Curved LED Video Wall

Planar® CarbonLight™ CLI Flex™ 1.3 is a pliable LED video wall display for smoothly-curved concave or convex video walls, waves, halos, domes or column wraps. It features a fine 1.3mm pixel pitch and a Glue-On-Board (GOB) protective treatment. It can form tight curves without color shift, offering a more visually appealing alternative to faceting flat LED cabinets into segmented curves.



| SPECIFICATION                           | DETAIL                           |
|---|----------------------------------|
| Model                                   | CLI1.3 Flex                      |
| Pixel Density (/m2)                     | 589,824/m2   63,488/ft2          |
| Module Resolution                       | 192x96                           |
| Module Size (W x H)                     | 250 x 125 mm                     |
| Power Consumption, Maximum (watts) SQ M | 600                              |
| Power Consumption, Typical (watts) SQ M | 200                              |
| Curve Diameter                          | 1,510mm                          |
| Line Voltage                            | 100~240v AC, 50/60Hz             |
| Module Weight (per display)             | ≤ .26lbs                         |
| Brightness Max, Calibration On (cd/sq)  | 600                              |
| Supported Frame rate                    | 50~60Hz                          |
| Color Temperature(K)                    | 3000-9000 adjustable             |
| Contrast Ratio                          | 4000:1                           |
| Viewing Angle (50% of                   | >140° horizontal; >140° vertical |

|   |   |
|---|---|
| brightness)   |   |
| Refresh Rate  | 3840Hz  |
| GOB   | Required  |
| Grey Scale  | 14 bit  |
| LED Lifetime (Half Brightness)                                  | 100,000 hours   |
| Operating Temperature/Humidity (degrees F/C, relative humidity) | -20° to 40° C   -4° to 104° F (10-80% RH, non-condensing)   |
| Storage Temperature/Humidity (degrees F/C, relative humidity)   | -35° to 60° C   -31° to 140° F (10-85% RH, non-condensing)  |
| Warranty  | 3 years; 24-hour customer service   |
| HDMI®   | Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. |

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 5/18/2024*

*© Copyright 2024 Planar Systems, Inc. All rights reserved*