

# Leyard DirectLight

## DL2-1.8

### LED Video Wall System

The Leyard® DirectLight® DL2-1.8 is a fine pitch LED video wall display with a 1.8 millimeter pixel pitch. With a 27" cabinet, it features a 16:9 aspect ratio designed for Ultra HD resolution. The Leyard DirectLight DL2-1.8 includes a mounting system for wall mounting and is fully front-serviceable. With an off-board design and redundant power supplies, the Leyard DirectLight DL2-1.8 is less than 4-inches deep when installed.



SPECIFICATION	DETAIL
<b>Product Name</b>	DL2-1.8
<b>Pixel Pitch</b>	1.875mm
<b>LED Type</b>	Commercial grade 3-in-1 Black SMD
<b>Cabinet Resolution</b>	320 x 180
<b>LEDs per Cabinet</b>	57,600
<b>Pixel Density</b>	284,444 / sq m   26,426 / sq ft
<b>Cabinet Size (W x H x D)</b>	600 x 337.5 x 95mm   23.62 x 13.28 x 3.74in
<b>Cabinet Diagonal</b>	688.5mm   27.1in
<b>Cabinet Area</b>	0.2025/sq m   2.18/sq ft
<b>Modules/Cabinet (W x H)</b>	2 x 2
<b>Module Resolution</b>	160 x 90
<b>LEDs per Module</b>	14,440
<b>Module Size</b>	300 x 168.75mm   11.81 x 6.64in
<b>Power Consumption, Maximum (watts)</b>	150 / Cabinet   741 / sq m
<b>Power Consumption, Typical (watts)</b>	50 / Cabinet   247 / sq m
<b>Line Voltage</b>	100-240V AC, 50/60Hz autoranging
<b>Cabinet Weight (per display)</b>	6.6 kg   14.5 lb
<b>Cabinet Weight (per m<sup>2</sup>)</b>	32.6 kg / sq m   71.6 lbs / sq m

<b>Mount Weight per Cabinet (kg / display)</b>	3.2 kg   7 lb
<b>Mount Weight per Cabinet (kg / sq m)</b>	15.8 kg / sq m   34.6 lbs / sq m
<b>Mounted Depth</b>	<4", ADA Compliant
<b>Brightness Max (cd / sq m)</b>	>800
<b>Contrast Ratio</b>	> 6,000:1
<b>Brightness Uniformity</b>	>97%
<b>Color Uniformity</b>	>97%
<b>Color Gamut</b>	100% NTSC
<b>LED Refresh Rate</b>	3,000 Hz
<b>Color Temperature, Adjustable (k)</b>	3,200 - 9,300
<b>Viewing Angle, Horizontal</b>	160°
<b>Viewing Angle, Vertical</b>	140°
<b>LED Surround</b>	Leyard® MicroGrid Shader™
<b>Video Inputs</b>	2x HDMI in, 2x HDMI out; HDCP Compliant
<b>Video Input Resolution Maximum</b>	1920 x 1080 @ 60Hz
<b>Frame Rate</b>	50, 60Hz
<b>Control Input Type</b>	RS232 or Ethernet
<b>Gray Scale Processing</b>	16-bit per color processing, 10-bit per color displayed
<b>Installation and Service Access</b>	Front
<b>LED Lifetime: Typical</b>	100,000 hrs
<b>Environment</b>	Indoor
<b>Power Supply</b>	Offboard   Redundant Optional   Hot Swap
<b>Wall Mount</b>	Leyard® EasyAlign™, Included
<b>Protection</b>	IP30
<b>Acoustic Noise</b>	Fanless Operation
<b>Operating Temperature/Humidity (degrees F/C) 10-80% relative humidity, non-condensing</b>	-10° to 40° C   -14° to 104° F
<b>Storage Temperature/Humidity (degrees F/C) 10-85% relative humidity, non-condensing</b>	-20° to 60° C   -4° to 140° F
<b>Regulatory Compliance</b>	NRTL UL 60950-1, FCC Class A, CE EN60950-1, EN 55032 Class A and EN 55024, WEEE, CISPR 32/2015

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 11/18/2018*

*© Copyright 2018 Planar Systems, Inc. All rights reserved*