



# Planar WallDirector VC4-L-F10G

VC4-L-F10G

Planar® WallDirector™ VC4-L-F10G is a compact and scalable video processor designed to drive up to four Full HD Planar video wall display sections using the powerful web-based Planar® WallDirector™ Software management application.



SPECIFICATION	DETAIL
Model Name	VC4-L-F10G
Supported Video Walls	Planar DirectLight Pro Series
Cabinet Size	1U rack-mounted controller, 19" rack
Maximum Output Resolution	Up to 8 Full HD (1920x1080) display section via fiber to cat converter. Max 16.6m pixels
Video Inputs	4x HDMI 2.0 (w/ HDCP 2.2)
Video Outputs	4x 10Gb Fiber
High Speed Link (HSL)	2 Out, 2 In QSFP+ Cabinet
HSL Loop Capacity	80Gb 4x 4K Full HD video sources
Fiber to Cat Converter	T10-SL-C5G
Maximum Distance from Video Wall	6561ft (2km)
Control	IR Remote Control, RS-232, USB, Network, Planar WallDirector

	Software Planar WallDirector Software
<b>Controller Status</b>	Diagnostic LEDs, WallDirector health monitoring and alerts
<b>Sync</b>	Mini BNC In/Out
<b>Image Scaling</b>	Planar Big Picture Plus windowing, Planar WallSync™ , PiP, 4K at 60Hz upscaling and downscaling
<b>Windowing</b>	13 per Video Controller
<b>Height</b>	1.7"/44mm
<b>Width</b>	19"/483mm
<b>Depth</b>	10.2"/260mm
<b>Weight</b>	8lbs/3.6kg
<b>Operating Temperature</b>	14°F to 104°F, -10°C to 40°C
<b>Storage Temperature</b>	-4°F to 185°F, -20°C to 85°C
<b>Operating Altitude</b>	0-10,000ft, 0-3,000m
<b>Operating Humidity</b>	20-80% RH

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 5/12/2024*

*© Copyright 2024 Planar Systems, Inc. All rights reserved*