

| | |
|--------------------------------|--|
| Audio Output | 1W x 2 |
| External Connections | HDMI 19-pin, DisplayPort 20-pin, VGA 15-pin, 3.5 mm audio in, 3.5mm headphone out |
| Compatibility | PC and Mac® (adapter may be required for Mac) |
| Power Supply | Internal |
| Power Consumption (max) | 23 Watt typical (0.5 Watt standby) |
| Power Requirements | AC 100/240 VAC |
| Operating Temperature | 0° to +40°C (32° to 104°F) |
| Humidity | 10 - 90% RH (non-condensing) |
| Mount | Built-in 100mm VESA, monitor back |
| Product Approvals | FCC-B, UL/cUL, RoHS |
| Recommended Usage | Up to 16 hours per day |
| Service and Support | 3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only). Please see warranty document for more details and for replacement procedures outside the US. |
| Options / Features | Wide color consistent viewing angle, Uniform bezel, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot |
| In the Box | PXL2270MW 21.5" LED LCD Monitor, Power cord, VGA cable, DP cable, audio cable, and User's guide |
| UPC | 8 10689 00239 0 |

Discontinued

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 6/22/2021

© Copyright 2021 Planar Systems, Inc. All rights reserved

Planar utilizes HDMI® standards in this product.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.