



# PLL1911M

## 19" LCD Monitor

The Planar® PLL1911M 19" LED LCD monitor features a 5:4 aspect ratio, dual input, integrated speakers, and an adjustable stand that makes it perfect for business applications.



SPECIFICATION	DETAIL
<b>Product Name</b>	PLL1911M
<b>Planar Part Number</b>	997-7451-00
<b>Viewable Size</b>	19" diagonal (14.81" horizontal x 11.85" vertical)
<b>Aspect Ratio</b>	5:4
<b>Contrast Ratio (typ)</b>	1000:1
<b>Viewing Angle (typ)</b>	178° Horizontal and 178° Vertical (Specified at CR>10:1)
<b>Response Time (typ)</b>	5 ms (GTG)
<b>Brightness (Typical)</b>	250 cd/m <sup>2</sup>
<b>Display Type</b>	IPS LCD Active Matrix Flat Panel Display (TFT)
<b>Display Resolution</b>	1280 x 1024 SXGA
<b>Tilt Range</b>	-5° to +19°
<b>Palette</b>	16.7 million colors
<b>Pixel Pitch</b>	0.294 mm
<b>Refresh Rate</b>	55~76 Hz (60 Hz recommended)
<b>Dimensions (W x H x D)</b>	16.0" x 16.7" x 8.5" (height can be adjusted to 20.3"); 406.4 mm x 424.2 mm x 215.9 mm (adjusted to 515.6 mm)
<b>Dimensions without Stand</b>	16.0" x 13.8" x 2.4" (406.4 mm x 350.5 mm x 61.0 mm)
<b>Panel Depth</b>	2.4" (61.0 mm)
<b>Display Weight</b>	8.2 lb (3.7 kg) , 6.2 lb (2.8 kg) without base & stand
<b>Shipping weight</b>	10.6 lb (4.8 kg)
<b>Video Inputs</b>	Digital (DVI-D w/HDCP), Analog (VGA)

<b>HDCP</b>	Yes
<b>External Connections</b>	(1) DVI 24-pin connector, (1) Analog VGA D-sub 15-pin video display, (1) 1/8 inch audio input jack
<b>Audio Output</b>	1w x 2
<b>Compatibility</b>	PC and Mac® (adapter may be required for Mac)
<b>Power Supply</b>	Internal
<b>Power Consumption (max)</b>	21W typical (standby 0.5W)
<b>Power Requirements</b>	AC 100/240 VAC
<b>Operating Temperature</b>	0° to +40°C (32° to 104°F)
<b>Humidity</b>	10 - 90% RH (non-condensing)
<b>Mount</b>	Built-in 100 mm VESA, back
<b>Product Approvals</b>	FCC-B, CE, UL/cUL, RoHS
<b>Recommended Usage</b>	Up to 16 hours per day
<b>Service and Support</b>	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only). Please see warranty document for more details and for replacement procedures outside the US.
<b>Options / Features</b>	Height adjustable stand, Supports Portrait, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot
<b>In the Box</b>	PLL1911M 19" LED LCD Monitor, Power Cord, VGA Cable, DVI Cable, Audio Cable, User's Guide
<b>Humidity</b>	10 - 90% RH (non-condensing)

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 12/6/2019*

*© Copyright 2019 Planar Systems, Inc. All rights reserved*