



# Planar VM Complete LCD Video Wall



## Bundled, High Performance LCD Video Walls

Planar® VM Complete™ video walls minimize the amount of time and effort required to select the right high-definition LCD video wall solution for any high-ambient light, 24x7 environment. Instead of compiling all the elements of the video wall separately, and determining which configuration would be best, Planar VM Complete video walls are pre-packaged with everything you need in one model. They also feature our popular Planar® VM Series LCD video wall displays.

A Planar VM Complete LCD video wall comes in a 2x2 or 3x3 array complete with a Full HD 49" or 55" Planar VM Series displays, mounts and trim pre-bundled, for a great value.



## Bezeled Beauty

Planar VM Complete video walls feature LCD video wall displays with tiled bezel widths of 0.88, 1.8 or 3.5 millimeters. The narrow tiled bezels create a near-seamless Full HD viewing experience even at close distances, with the 0.88 millimeter tiled bezel models being the thinnest in the industry. With diagonal video wall size options ranging from 97" to 164", mountable in landscape orientation, there is surely a Planar VM Complete bundle ideal for most any retail store, hospitality setting, or corporate lobby.

## Bright When It's Light Out

Planar VM Complete video walls have brightness options from 450 to 700 nits for optimized viewing in different ambient light such as darker museums or bright hotels. And the bright displays won't waste energy as they are ENERGY STAR® certified.



## Bundle and Save

Selecting an off-the-shelf Planar VM Complete video wall not only saves time, energy and the challenges associated with designing a video wall, but it also saves budget as the seven Planar VM Complete models cost less than purchasing the same video wall components a la cart.

- Complete Full HD LCD video wall ready to install
- Available in two sizes – 49" or 55", three tiled bezel widths and three brightness options
- Includes video wall displays, mounts and trim
- Brightness from 450 nits to 700 nits for most ambient light settings
- Tiled bezel widths as small as 0.88 millimeters
- Video wall display models are ENERGY STAR® certified



| Model     | Display Diagonal | Configuration | Total Diagonal* | Tiled Bezel Width | Brightness | ENERGY STAR Display |
|-----------|------------------|---------------|-----------------|-------------------|------------|---------------------|
| VMC55MXM9 | 55"              | 3x3           | 164"            | 0.88mm            | 700 nits   | Yes                 |
| VMC55MXM4 | 55"              | 2x2           | 109"            | 0.88mm            | 700 nits   | Yes                 |
| VMC55LXU9 | 55"              | 3x3           | 164"            | 3.5mm             | 500 nits   | Yes                 |
| VMC55LXU4 | 55"              | 2x2           | 109"            | 3.5mm             | 500 nits   | Yes                 |
| VMC49MXX9 | 49"              | 3x3           | 146"            | 1.8mm             | 700 nits   | Yes                 |
| VMC49MXX4 | 49"              | 2x2           | 97"             | 1.8mm             | 700 nits   | Yes                 |
| VMC49LXU4 | 49"              | 2x2           | 97"             | 3.5mm             | 450 nits   | Yes                 |

\*These are estimates only. Please refer to the display and mount dimensional drawings and display spacing guidance as found in the Planar VM Series User Guide.