



- 3. 200-240V_{ac} RANGE, MAX OUTPUT IS 7600W
 - 2. PROPER SUPPORT MUST BE USED WHEN INSTALLING IN A RACK.
 - 1. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.
- NOTES: UNLESS OTHERWISE SPECIFIED.



THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO PLANAR SYSTEMS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF PLANAR SYSTEMS IS PROHIBITED. THIS DRAWING IS SUPPLIED FOR INFORMATION, IDENTIFICATION, ENGINEERING, EVALUATION, AND/OR INSPECTION PURPOSES ONLY AND MAY NOT BE USED AS BASIS FOR THE MANUFACTURING OF PRODUCTS OR THE FURNISHING OF SERVICES TO PLANAR SYSTEMS OR TO ANY THIRD PARTY UNLESS AUTHORIZED IN WRITING BY PLANAR SYSTEMS.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS (INCHES)		ENGR BY		 PLANAR SYSTEMS, INC. 1195 NE COMPTON DRIVE HILLSBORO, OR 97006 USA
TOLERANCES:		DRAWN BY	28SEP16	
X= ±1	XX= ±.25	CHECKED BY	EJS	TITLE RPS220 POWER SUPPLY OUTLINE
.X= ±.5	∠= ±1°	USED ON		
DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994		MATERIAL		SIZE D
THIRD ANGLE PROJECTION		FINISH		PART NO -
				DRAWING NO. -
				REV B
				SCALE 1:3
				DO NOT SCALE
				SHEET 2 OF 3




DETAIL B
SCALE 4 : 1

RPS110 FULLY POPULATED REDUNDANT 1RU SHOWN



DETAIL A
SCALE 4 : 1

RPS220 FULLY POPULATED REDUNDANT 1.5RU SHOWN



WIRE LIST		
FROM	TO	AWG
P1-1	P2-1	10
P1-2	P2-2	10

4. AUX DC POWER 48V, 4A MAX
PINS 1 AND 2 ARE + (POSITIVE); PINS 3 AND 4 ARE - (GROUND).
 3. AC POWER CABLES INCLUDED WILL BE ONE OF THE FOLLOWING:
US: 15FT NEMA 15-5P TO IEC C19
UK: 2.5M BS 1363 TO IEC C19
EU: 3M CEE 7/7 TO IEC C19
 2. MAXIMUM POWER CABLE LENGTH TO FIRST DISPLAY:
REFER TO FINAL CONFIGURATION FOR MAXIMUM ALLOWED.
 1. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.
- NOTES: UNLESS OTHERWISE SPECIFIED.