

## Planar PXL2471MW

24" LCD Monitor

The Planar® PXL2471MW 24" LED LCD monitor is Planar's most comprehensive product in our desktop line up. Not only is it energy-efficient and green for the environment, it features full connectivity including VGA, HDMI, DisplayPort, an ergonomically designed, height-adjustable stand, and speakers.



| SPECIFICATION            | DETAIL   |
|--------------------------|--|
| Product Name             | PXL2471MW  |
| Planar Part Number       | 997-7848-01  |
| Viewable Size            | 23.8" diagonal   |
| Aspect Ratio             | 16:9   |
| Contrast Ratio (typ)     | 1000:1   |
| Viewing Angle (typ)      | 178° Horizontal and 178° Vertical (Specified at CR>10:1) |
| Response Time (typ)      | 5 ms (GTG)   |
| Brightness (Typical)     | 250 cd/m²  |
| Display Type             | IPS LCD Active Matrix Flat Panel Display (TFT)           |
| Display Resolution       | Full HD 1080p, 1920 x 1080                               |
| Tilt Range               | -5° to +15°  |
| Palette                  | 16.7 million colors                                      |
| Pixel Pitch              | 0.2715 mm  |
| Refresh Rate             | 55~76 Hz (60 Hz recommended)                             |
| Dimensions (W x H x D)   | 22.1" x 15.2" X 8.4" (561.3 mm x 386.1 mm x 213.4 mm)    |
| Dimensions without Stand | 22.1" x 13.1" x 2.1" (561.3 mm x 332.7 mm x 53.3 mm)     |
| Panel Depth              | 2.1" (53.3 mm)   |
| Display Weight           | 12.6 lb/5.7 kg (8.2 lb/3.7 without base and stand)       |
| Shipping weight          | 15.5 lb (7 kg)   |
| Video Inputs             | HDMI, DisplayPort, VGA                                   |
| HDCP                     | Yes  |

| Audio Output            | 1w x 2  |
|-------------------------|---|
| External Connections    | HDMI 19-pin, DisplayPort 20-pin, VGA 15-pin, 3.5 mm audio in, 3.5mm headphone out   |
| Compatibility           | PC and Mac® (adapter may be required for Mac)   |
| Power Supply            | Internal  |
| Power Consumption (max) | 32 Watt typical (0.5 Watt standby)  |
| Power Requirements      | AC 100/240 VAC  |
| Operating Temperature   | 0° to +40°C (32° to 104°F)  |
| Humidity                | 10 - 90% RH (non-condensing)  |
| Mount                   | Built-in 100mm VESA, monitor back   |
| Product Approvals       | FCC-B, CE, UL/cUL, RoHS   |
| Recommended Usage       | Up to 16 hours per day  |
| Service and Support     | 3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only). Please see warranty document for more details and for replacement procedures outside the US.  |
| Options / Features      | Wide color consistent viewing angle, Uniform bezel, Discreet branding, Glossy finish, height adjustment: 4.3" (110cmm), Swivel range 90° (45° left, 45° right), pivot 90°, anti-glare coating, multi-language display, on screen display (OSD), Kensington® Security Slot |
| Blue Light Reduction    | Yes   |
| In the Box              | PXL2471MW 23.6" LED LCD Monitor, Power cord, VGA cable, DP cable, audio cable, and User's guide   |
| UPC                     | 8 10689 00221 5   |