

HDCP	Yes
Audio Output	Integrated 2W/channel stereo speakers, headphone jack
External Connections	DVI 24-pin, DisplayPort 20-pin, HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5mm headphone out
Compatibility	FOR PC: VGA Support up to 2048 x 1152, HDMI Support up to 1920 x 1080, DVI-D/ DP support up to 2560 x 1440 (non-interlaced); FOR MAC: VGA Support up to 2048 x 1152, HDMI Support up to 1920 x 1080, DVI-D/ DP Support up to 2560 x 1440 (Note: For Mac® OSX 10.8.3, DVI-D only supports up to 1920 x 1080)
Power Supply	Internal
Power Consumption (max)	31W (<0.5W standby)
Power Requirements	AC 100/240 VAC
Operating Temperature	0° to +40°C (32° to 104°F)
Humidity	10 - 90% RH (non-condensing)
Mount	Built-in 100 mm VESA, back
Product Approvals	UL/c-UL, FCC-Class B, CE, RoHS
Recommended Usage	Up to 16 hours per day
Service and Support	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only). Please see warranty document for more details and for replacement procedures outside the US.
Options / Features	IPS panel, Wide color consistent viewing angle, Discreet branding, Multi-language display, On screen display (OSD), Kensington® Security Slot
Blue Light Reduction	Yes
Flicker Free	Yes
In the Box	PXL2780MW 27" LED LCD Monitor, Power Cord, DVI-Dual Link Cable, DisplayPort Cable, Audio cable, User's Guide
UPC	8 10689 00221 3

Discontinued

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 10/21/2020

© Copyright 2020 Planar Systems, Inc. All rights reserved

Planar utilizes HDMI® standards in this product.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.