

Audio Output	1w x 2
External Connections	HDMI 19-pin, DisplayPort 20-pin, VGA 15-pin, 3.5 mm audio in, 3.5mm headphone out
Compatibility	PC and Mac® (adapter may be required for Mac)
Power Supply	Internal
Power Consumption (max)	32 Watt typical (0.5 Watt standby)
Power Requirements	AC 100/240 VAC
Operating Temperature	0° to +40°C (32° to 104°F)
Humidity	10 - 90% RH (non-condensing)
Mount	Built-in 100mm VESA, monitor back
Product Approvals	FCC-B, CE, UL/cUL, RoHS
Recommended Usage	Up to 16 hours per day
Service and Support	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only). Please see warranty document for more details and for replacement procedures outside the US.
Options / Features	Wide color consistent viewing angle, Uniform bezel, Discreet branding, Glossy finish, height adjustment: 4.3" (110cmm), Swivel range 90° (45° left, 45° right), pivot 90°, anti-glare coating, multi-language display, on screen display (OSD), Kensington® Security Slot
Blue Light Reduction	Yes
In the Box	PXL2471MW 23.6" LED-LCD Monitor, Power cord, VGA cable, DP cable, audio cable, and User's guide
UPC	8 10689 00221 5

Discontinued

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 10/21/2020

© Copyright 2020 Planar Systems, Inc. All rights reserved

Planar utilizes HDMI® standards in this product.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.