

Planar TWA1.8

LED Video Wall

The Planar® TWA1.8 is a fine pitch LED video wall display with a 1.8 millimeter pitch. The Planar TWA1.8 delivers benefits unique to its “flat panel” design including enhanced image quality, a 16:9 form factor optimized for the most popular high resolutions, ease of installation and service, and outstanding flatness and uniformity. With a power-efficient design, the Planar TWA1.8 significantly reduces power utilization while delivering additional image optimization features.



Specification:

Detail:

Product Name	TWA1.8
Pixel Pitch	1.875mm
LED Type	Commercial grade 3-in-1 Black SMD
Cabinet Resolution	640 x 360
LEDs per Cabinet	230,400
Pixel Density	284,444 / sq m 26,422 / sq ft
Cabinet Size (W x H x D)	1,200 x 675 x 100mm 47.24 x 26.57 x 3.94in
Cabinet Diagonal	1,377mm 54.21in
Cabinet Area	0.81 sq m 8.718 sq ft
Modules/Cabinet (W x H)	5 x 4
Module Resolution	128 x 90

Specification:

Detail:

LEDs per Module	11,520
Module Size	240 x 168.75mm 9.44 x 6.64in
Power Consumption, Maximum	440 / Cabinet 543 / sq m
Power Consumption, Typical (watts)	132/ Cabinet 162 / sq m
Line Voltage	100-240V AC, 50/60Hz autoranging
Cabinet Weight (per display)	30 kg 66.1 lb
Cabinet Weight (per m²)	37 kg / sq m 81.6 lbs / sq m
Brightness Max (cd / sq m)	800
Contrast Ratio	> 6,000:1
Brightness Uniformity	>97%
Color Uniformity	>97%
Color Gamut	100% NTSC
LED Refresh Rate	5100 Hz
Color Temperature, Adjustable (k)	3,200 - 9,300
Viewing Angle, Horizontal	160°
Viewing Angle, Vertical	140°
LED Surround	Planar® MicroGrid Shader™
Video Inputs	2x HDMI in, 2x HDMI out; HDCP Compliant
Video Input Resolution Maximum	1920 x 1080 @ 60Hz
Frame Rate	50, 60Hz
Control Input Type	RS232 or Ethernet
Gray Scale Processing	16-bit
Service Access	Rear

Specification:

LED Lifetime (Half Brightness)
Environment
Power Supply
Protection
Acoustic Noise
Operating Temperature/Humidity (degrees F/C) 10-80% relative humidity, non-condensing
Storage Temperature/Humidity (degrees F/C) 10-85% relative humidity, non-condensing
Regulatory Compliance
Warranty
HDMI®

Detail:

100,000 hrs
Indoor
Single. Dual optional
IP30
Fanless Operation
-10° to 40° C 14° to 104° F
-20° to 60° C -4° to 140° F
NRTL UL 60950-1, FCC Class A, CE EN60950-1, EN 55032 Class A and EN 55024, WEEE, CISPR 32/2015
3 years; 24-hour customer service
Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Planar is a trademark of Planar Systems, Inc. All other trademarks and service marks are property of their holders. Copyright © 2025 Planar Systems, Inc. All rights reserved. This document may not be copied in any form without permission from Planar. Information in this document is subject to change without notice.