



Standard Models

	Planar® UltraRes™ P Series	Planar® UltraRes™ W Series	Planar® Simplicity™ P Series	Planar® Simplicity™ E Series
Sizes	49", 55", 65", 75", 86", 98"	105"	43", 50", 55", 65", 75", 86"	43", 50", 55", 65", 75", 86", 98"
Brightness	✓ 700 nits	500 nits	500 nits	500 nits
Color Gamut	90%	88%	72%	DCI-P3 90%
HDR	✓	✓	--	--
Orientation	✓ Landscape, Portrait	✓ Landscape, Portrait	✓ Landscape, Portrait	✓ Landscape, Portrait
U.S. TAA Compliant	✓	✓	--	--
ENERGY STAR® Certified	✓	✓	✓	✓
Security Features	✓ Signed & Encrypted Firmware: All can disable communication interfaces, SSH*	✓ Signed & Encrypted Firmware, Can disable communication interfaces EN 303 645 certified	✓ Secure Shell (SSH) protocol, EN 303 645 certified	--
Outputs	--	✓ DisplayPort 1.4	--	--
Inputs: OPS	--	✓	--	--
Inputs: DisplayPort	✓ DP2.0	✓ DP1.4	--	--
Inputs: HDMI®	✓ HDMI 2.1	✓ HDMI 2.0, HDMI 2.1	✓ HDMI 2.0	✓ HDMI 2.0
Inputs: HDMI-CEC	✓	✓	✓	✓
Inputs: HDCP 2.2	✓	✓	✓	✓
Inputs: LAN RJ45, RS232	✓	✓	✓	✓
Inputs: WiFi, BlueTooth®	--	--	--	✓
Inputs: USB	✓	--	✓ USB, MicroSD, internal storage, web page and embedded cloud-based content app (requires subscription)	✓
Inputs: USB-C	✓	✓	✓	--
Image adjustments by source	✓	✓	--	--
Scheduling	✓	✓	✓	✓
Presets	✓	--	--	
Media Playback	--	✓ via OPS	✓ USB	✓ USB
Browser	--	✓ via OPS	✓	✓
SNMP²	✓	✓	--	--
Remote Monitoring³ (email notifications)	✓	✓	--	--
Audio Speakers	✓	✓	✓	✓
24x7 Operation	✓	✓	✓	✓
Metal Enclosure	✓	✓	✓ Rear enclosure	✓ Select models
Warranty Included	✓ 3-year	✓ 3-year	✓ 3-year	✓ 3-year
Ideal Applications	Digital branding & signage Collaboration Education Retail Public spaces	Digital branding & signage Collaboration Education Retail Public spaces	Retail Medical offices Reception areas Restaurants Hospitality	Digital branding & signage Education Wayfinding Restaurants Public spaces

*Planar ERO-LCD™ protection — Proprietary, optically bonded protective glass process that improves contrast and overall durability for high-traffic environments

²SSH - Secure Shell Protocol

³SNMP - Simple Network Managing Protocol, allows monitoring and control of the display over a network

³Remote Monitoring — subset of SNMP; diagnostics for individual display components and display settings



Interactive Touch Models

	Planar® UltraRes™ P Series Touch	Planar® UltraRes™ W Series Touch	Planar® Simplicity™ P Series Touch
Sizes	49", 55", 65", 75", 86", 98"	105"	43", 50, 55", 65", 75", 86"
Touch technology	✓ Projected Capacitive (PCAP)	✓ Projected Capacitive (PCAP)	✓ Projected Capacitive (PCAP)
Touch points, simultaneous	50 points	50 points	20 points
Fine Tip Stylus Support	✓ Passive stylus (included)	✓ Passive stylus (included)	✓ Passive stylus (included)
Brightness (with touchscreen)	700 nits	450 nits	400 nits
Color Gamut	90%	88%	72%
HDR	✓	✓	--
Orientation	✓ Landscape, Portrait	✓ Landscape, Portrait	✓ Landscape, Portrait
Cover Glass	✓ *3mm, AG Coating	✓ *3mm, AG + AF Coating	✓ 2mm, AG Coating
U.S. TAA Compliant	✓	✓	--
ENERGY STAR® Certified	✓	✓	✓
Security Features	✓ Signed & Encrypted Firmware: All can disable communication interfaces, SSH*	✓ Signed & Encrypted Firmware: Can disable communication interfaces EN 303 645 certified	✓ Secure Shell (SSH) protocol, EN 303 645 certified
Outputs	--	✓ DisplayPort 1.4	--
Inputs: OPS	--	✓	--
Inputs: DisplayPort	✓ DP2.0	✓ DP1.4	--
Inputs: HDMI®	✓ HDMI 2.1	✓ HDMI 2.0, HDMI 2.1	✓ HDMI 2.0
Inputs: HDMI-CEC	✓	✓	--
Inputs: HDCP 2.2	✓	✓	✓
Inputs: LAN RJ45, RS232	✓	✓	✓
Inputs: USB	✓	✓	✓
Inputs: USB-C	✓	✓	✓
Image adjustments by source	✓	✓	--
Scheduling	✓	✓	✓
Presets	✓	--	--
Media Playback	--	--	✓ USB, MicroSD, internal storage, web page and embedded cloud-based content app (requires subscription)
Browser	--	--	✓
SNMP²	✓	✓	--
Remote Monitoring³ (email notifications)	✓	✓	--
Audio Speakers	✓	✓	✓
24x7 Operation	✓	✓	✓
Metal Enclosure	✓	✓	✓ Rear enclosure
Warranty Included	✓ 3-year	✓ 3-year	✓ 3-year

*Planar ERO-LCD™ protection — Proprietary, optically bonded protective glass process that improves contrast and overall durability for high-traffic environments

*SSH - Secure Shell Protocol

²SNMP- Simple Network Managing Protocol, allows monitoring and control of the display over a network

³Remote Monitoring — subset of SNMP; diagnostics for individual display components and display settings

HDMI® — The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.