

# Planar TVF Complete HD 137

**LED Video Wall**

The Planar<sup>®</sup> TVF Complete<sup>™</sup> HD 137 is a Full HD, 137" LED video wall solution that includes everything an organization needs to deliver large-format beautiful video and imagery, in less time and with less effort. The solution comes with LED display cabinets, cables, spare modules, wall mounts, trim, remote control and full-featured video controller all included. The Planar TVF Complete HD 137 features front-side installation and serviceability for easier access and installation against the wall.



Specification:

Detail:

<b>Part Number</b>	998-2602
<b>Product Name</b>	HD 137
<b>Display Technology</b>	Direct View LED
<b>Display Resolution</b>	1920 x 1080

Specification:

Detail:

<b>Image Size (diagonal)</b>	137"
<b>Display size</b>	3024 x 1701mm   9.9' x 5.6'
<b>Pixel Pitch</b>	1.575mm
<b>Brightness Max (cd / sq m)</b>	600 nits
<b>Contrast Ratio</b>	7000:1
<b>Brightness Uniformity</b>	≥97%
<b>Color Uniformity</b>	≥97%
<b>LED Refresh Rate</b>	3000
<b>Color Temperature, Adjustable (k)</b>	3000 - 10000
<b>Viewing Angle, Horizontal</b>	160°
<b>Viewing Angle, Vertical</b>	140°
<b>Video Input Resolution Maximum</b>	3840 x 2160 @ 60Hz
<b>HDR Support</b>	HDR10
<b>Frame Rate</b>	50, 60Hz
<b>Video Inputs</b>	4x HDMI 2.0 (HDCP 2.2), 1x DisplayPort 1.2
<b>HDMI®</b>	Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.
<b>Control</b>	RS232, Network

Specification:	Detail:
<b>Service Access</b>	Front
<b>Runtime Duty Cycle (Hours/Day)</b>	24 x 7
<b>LED Lifetime (Half Brightness)</b>	100,000 hrs
<b>Power Supply</b>	Redundant
<b>Line Voltage</b>	100~240V AC, 50/60Hz
<b>Power Consumption, Maximum (watts)</b>	3250
<b>Display Weight</b>	183kg  403lbs
<b>Environmental</b>	Indoor
<b>Storage Temperature/Humidity (degrees F/C, relative humidity)</b>	-20° to 60° C   -4° to 140° F 10-85% relative humidity, non-condensing
<b>Operating Temperature/Humidity (degrees F/C, relative humidity)</b>	-10° to 40° C   14° to 104° F 10-80% relative humidity, non-condensing
<b>Warranty</b>	Planar EverCare Lifetime Warranty (North America)
<b>Package Includes (solution and packaged content may vary by region)</b>	Display wall, Planar WallDirector Video controller, Signal cables, Power cables, Wall mount, Trim, Remote Control, and Module Spares