

Planar Luminate Ultra W Series

PLANAR

Outdoor Microl FD Video Wall

- Preconfigured 115", 145", 173" & 231" sizes
- Configurable with 1.3, 1.6 & 2mm pixel pitches
- 3,000-nit brightness
- **GOB** protective coating



Planar® Luminate™ Ultra W Series MicroLED video wall displays are designed to bring high-detail imagery and video to outdoor environments with close viewing distances. Their 16:9 aspect ratio is ideal for Full HD and 4K cinema and sports media, while fine pixel pitch supports comfortable viewing from as close as 8 feet. High brightness ensures visibility even in direct sunlight, and waterproof Glue-On-Board (GOB) technology withstands harsh outdoor environments.

High Bright, Fine Details

Planar Luminate Ultra W Series is suitable for every sunnyday application with its 3,000-nit brightness and fine pixel pitch. They are excellent for outdoor cinema, sports stadium concourse signage, quick-serve restaurant kiosks and more. They thrive in high ambient light indoor spaces as well.





MicroLED Might

Planar Luminate Ultra W Series features advanced MicroLED technology that delivers more brightness, excellent color uniformity, better overall contrast and deeper blacks.

MicroLEDs also use less power and produce less heat.



More Protection

The displays have a proprietary protective coating that fills the tiny gaps between LEDs adding ruggedness and weather resistance. The coating also increases visual contrast for darker black levels.



Added Assurance

Planar Luminate Ultra W Series video walls feature a 3-year LED Standard Limited Warranty, offering additional peace-of-mind investment protection.



Weatherproof

Planar Luminate Ultra W Series features an IP65 Ingress Protection Rating which means displays are dust tight and protected against even powerful water jets, making them an exciting and viable option in any weather.



Easy Access

Front-side installation and service shrink the overall video wall footprint and virtually eliminates servicing space needed behind the wall.



Off-the-Shelf or Design Your Own

Planar® Luminate Ultra W Complete™ video walls are available in Full HD 115″, 145″, 173″ and 4K 231″ sizes to reduce configuration time and complexity. Simply select a diagonal size and resolution and receive everything in one complete, no-hassle display solution.

If none of the preconfigured video walls is quite right, create custom sizes, shapes and resolutions using the 29" Planar Luminate Ultra W Series cabinets; available with 1.3, 1.6, & 2mm pixel pitches.



Specifications

-					
Preconfigured Model	HD 115	HD 145	HD 173	UHD 231	
Controller	Colorlight Z5				
Display Technology	MicroLED				
Dislpay Diagonal	115"	145"	173"	231"	
Display Size, with Mounts (W x H x D)	8.4' x 4.7' x 3.76"	10.5' x 5.9' x 3.76"	12.6′ x 7.1′ x 3.76″	16.8' x 9.4' x 3.76"	
Display Resolution	1920x1080 3840x2160			3840x2160	
Display Weight, with Mounts (lbs)	349	521	751	1,131	
Power Consumption Max	3,360	5,250	7,650	13,440	
Brightness Max, Calibration On (cd/sq)	3,000				
Supported Frame Rate	50 & 60Hz				
Color Temperature (k)	3,000-10,000 adjustable				
Luminance Variation (Uniformity-White)	97%				
Contrast	10,000:1				
Viewing Angle (50% brightness)	>170° horizontal; >170° vertical				
Front Access Installation/Service	Yes				
Refresh Rate	3,840Hz				
Operating Temperature/Humidity	-4° to 122° F -20° to 50° C (10-80% RH, non-condensing)				
Storage Temperature/Humidity	-31° to 140° F -35° to 60° C (10-85% RH, non-condensing)				
Ingress Protection Rating	IP65 Front/Back				
Video Input Resolution	4096 x 2160				
Runtime Duty Cycle (Hours/Days)	24x7				
Package Includes	Display wall, Video Controller, Wall mounts, Signal cables, Power cables, Trim, Spare module (May vary by region)				

Model	LUW 1.3	LUW 1.6	LUW 2.0		
Pixel Pitch (mm)	1.3	1.6	2.0		
LED Package	MicroLED				
Cabinet Size (W x H x D)	25.19" x 14.17" x 2.76" (640 x 360 x 70 mm)				
Cabinet Diagonal	28.9" (734.06mm)				
Cabinet Area (m²)	0.2				
Cabinet Resolution	480x270	384x216	320x180		
LEDs per Cabinet	129,600	82,944	57,600		
Modules/Cabinet (W x H)		4 x 1			
Module Resolution	120x270	96x216	80x180		
Module Size (W x H)	160x 360mm				
Power Consumption, Max (watts)	150				
Line Voltage	100~240v AC, 50/60Hz				
Cabinet Weight (per display)	≤17.64lbs				
Cabinet Weight (per m²)	≤ 70.55lbs				
Mounting Orientation	Wall, Faceted				
Installation/Service Access	Front & Rear				
LED Lifetime (50% brightness)	100,000 hrs				

