



PLL1500M

15" LCD Monitor

The Planar® PLL1500M professional LED LCD monitor features a thin, professional design, internal power supply, integrated speakers, and analog input. The brightness, resolution, and contrast ratio enable expanded application possibilities.



| SPECIFICATION | DETAIL |
|---------------------------------|--|
| Product Name | PLL1500M |
| Planar Part Number | 997-7318-01 |
| Viewable Size | 15" diagonal (11.97" x 8.98") (304.04 mm x 228.09 mm) |
| Aspect Ratio | 4:3 |
| Contrast Ratio (typ) | 700:1 |
| Viewing Angle (typ) | 160° Horizontal and 130° Vertical |
| Response Time (typ) | 8 ms |
| Brightness (Typical) | 300 cd/m ² |
| Display Type | Edge-Lit LED LCD |
| Display Resolution | 1024 x 768 XGA |
| Tilt Range | -1° to +20° |
| Palette | 16.2 million colors |
| Pixel Pitch | 0.297 mm |
| Refresh Rate | 55-76Hz (60Hz recommended) |
| Dimensions (W x H x D) | 13.35" x 13.68" x 5.81" (339 mm x 347.40 mm x 147.48 mm) |
| Dimensions without Stand | 13.35" x 11.28" x 2.04" (339 mm x 286.50 mm x 51.70 mm) |
| Panel Depth | 2.04" (51.7 mm) |
| Display Weight | 6.6 lbs (3 kgs) , 5.7 lbs (2.6 kgs) without base & stand |
| Shipping weight | 8.8 lbs. (4kgs) |
| Video Inputs | Analog |

| | |
|--------------------------------|--|
| External Connections | 1 Analog VGA D-sub 15-pin video display |
| Audio Output | Yes, stereo speakers 1W per channel |
| Compatibility | PC and Mac® (adapter may be required for Mac) |
| Power Supply | Internal |
| Power Consumption (max) | 8W Typical, (0.5 watt Standby) |
| Power Requirements | AC 100/240 VAC |
| Operating Temperature | 0° to +40°C (32° to 104°F) |
| Humidity | 10 - 90% RH (non-condensing) |
| Mount | Built-in 75 mm VESA, back |
| Product Approvals | FCC-B, CE, UL/cUL, RoHS |
| Recommended Usage | Up to 16 hours per day |
| Service and Support | 3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only). Please see warranty document for more details and for replacement procedures outside the US. |
| Options / Features | Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot |
| Blue Light Reduction | Yes |
| In the Box | PLL1500M 15" LCD Monitor, Power Cord, VGA Cable, User's Guide |
| UPC | 8 10689 00226 0 |

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 9/22/2019

© Copyright 2019 Planar Systems, Inc. All rights reserved