



# PLL2450MW

## 24" LCD Monitor

The Planar® PLL2450MW 24" Full HD LCD desktop monitor features integrated TrueMedia™ speakers and VGA and HDMI video inputs. With its small footprint, it can be mounted on a multi-monitor stand for home, office or healthcare applications. It offers wide viewing angles and excellent color balance. Blue light reduction pre-sets help lower eye fatigue and maintain visual comfort. Its 100mm VESA compatibility pairs well with Planar accessories like Dual or Triple Monitor Stands.



SPECIFICATION	DETAIL
Product Name	PLL2450MW
Planar Part Number	997-9045-00
Viewable Size	23.6" diagonal (20.52" horizontal x 11.54" vertical)
Aspect Ratio	16:9
Contrast Ratio (typ)	3000:1
Viewing Angle (typ)	178° Horizontal and 178° Vertical (Specified at CR>10:1)
Response Time (typ)	12.5 ms (GTG)
Brightness (Typical)	250 cd/m <sup>2</sup>
Display Type	Edge-Lit LED LCD
Display Resolution	1920 x 1080, full HD
Tilt Range	-5° to +20°
Palette	16.7 million colors
Pixel Pitch	0.2715 mm
Refresh Rate	55-76Hz (60Hz recommended)
Dimensions (W x H x D)	21.6" x 16.0" x 6.7" (547.6 mm x 405.5 mm x 170.4 mm)
Dimensions without Stand	21.6" x 16.0" x 1.6" (547.6 mm x 405.5 mm x 40.9 mm)
Panel Depth	1.6" (40.9 mm)
Display Weight	6.9 lb (3.12 kg), 6.4 lb (2.87 kg) without base & stand
Shipping weight	8.5 lb (3.85 kg)
Video Inputs	HDMI, VGA
HDCP	Yes

<b>External Connections</b>	HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out
<b>Audio Output</b>	Integrated TrueMedia™ speakers, 1W/channel
<b>Compatibility</b>	PC and Mac® (adapter may be required for Mac)
<b>Power Supply</b>	Internal
<b>Power Consumption (max)</b>	18.5 Watts typical (<0.5W standby)
<b>Power Requirements</b>	AC 100/240 VAC
<b>Operating Temperature</b>	5° to +40°C (41° to 104°F)
<b>Humidity</b>	10 - 90% RH (non-condensing)
<b>Mount</b>	Built-in 100 mm VESA, back
<b>Product Approvals</b>	FCC-B, UL/cUL, RoHS
<b>Recommended Usage</b>	Up to 16 hours per day
<b>Service and Support</b>	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only). Please see warranty document for more details and for replacement procedures outside the US.
<b>Options / Features</b>	Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot
<b>Blue Light Reduction</b>	Yes
<b>Flicker Free</b>	Yes
<b>In the Box</b>	PLL2450MW 24" LED LCD Monitor, C5 Connector Power Cord, HDMI Cable, User's Guide
<b>UPC</b>	8 10689 00410 3

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 6/26/2022*

*© Copyright 2022 Planar Systems, Inc. All rights reserved*