



# PZD2410

## 24" Full HD USB Type-C Docking monitor

The slim Planar® PZD2410 is a 24" Full HD USB Type-C Docking monitor that provides an easy way to connect and power a PC/laptop. A single USB-C cable can deliver audio, video, data, network connectivity and up to 65 watts of power. The daisy-chain feature simplifies connecting another monitor. It is flicker free and incorporates blue light reduction presets to help lower eye fatigue. The ergonomic stand lets it fit nicely in education, home, office or healthcare applications.



SPECIFICATION	DETAIL
Product Name	PZD2410
Planar Part Number	998-2945-00
Viewable Size	23.8" diagonal (20.75" horizontal x 11.67" vertical)
Aspect Ratio	16:9
Contrast Ratio (typ)	1000:1
Viewing Angle (typ)	178° Horizontal and Vertical
Response Time (typ)	5 ms (GTG)
Brightness (Typical)	250 cd/m <sup>2</sup>
Display Type	IPS LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	Full HD 1080P, 1920 x 1080
Tilt Range	-5° to +20°
Palette	16.7 million colors
Pixel Pitch	0.2745 mm
Refresh Rate	48-75Hz (60Hz recommended)
Dimensions (W x H x D)	21.2" x 19.6" x 9.0" (539.5 mm x 498.3 mm x 228.9 mm)
Dimensions without Stand	21.2" x 12.7" x 2.0" (539.5 mm x 323.1 mm x 50.7 mm)
Panel Depth	2.0" (50.7 mm)
Display Weight	11.5 lb/5.2 kg (7.5 lb/ 3.4 kg without stand)
Shipping weight	15.7 lb (7.1 kg)
Video Inputs	USB Type C (DisplayPort Alt Mode), DisplayPort, HDMI
Video Outputs	DisplayPort
HDCP	Yes

<b>Audio Output</b>	Integrated 2W/channel stereo speakers, headphone jack
<b>External Connections</b>	USB Type C, HDMI 19-pin, DisplayPort 20-pin, 3.5mm headphone out, USB 3.2 Gen 2 (Type A) x 3 , RJ45, DisplayPort 20-pin (out)
<b>USB</b>	USB-C x 1 (Upstream) (10Gbps), USB3.2 Gen2 x 3 (Downstream with 1 fast charge BC 1.2)
<b>USB C Power Delivery</b>	USB C (Up to 65W) (5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3.25A)
<b>RJ45</b>	Ethernet LAN (10M/100M/1000M)
<b>Compatibility</b>	PC and Mac® (adapter may be required for Mac)
<b>Power Supply</b>	Internal
<b>Power Consumption (max)</b>	20W typical (<0.5W standby)
<b>Power Requirements</b>	AC 100/240 VAC
<b>Operating Temperature</b>	0° to +40°C (32° to 104°F)
<b>Humidity</b>	10 - 85% RH (non-condensing)
<b>Mount</b>	Built-in 100 mm VESA, back
<b>Product Approvals</b>	cTUVus, CE , FCC-B, RoHS
<b>Recommended Usage</b>	Up to 16 hours per day
<b>Service and Support</b>	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only). Please see warranty document for more details and for replacement procedures outside the US.
<b>Options / Features</b>	IPS panel, Wide color consistent viewing angle, Discreet branding, Height adjustment: 4.3" (120cmm), Swivel range 60° (30° left, 30° right), Pivot 90°, Anti-glare coating ,Multi-language display, On screen display (OSD), Kensington® Security Slot
<b>Blue Light Reduction</b>	Yes
<b>Flicker Free</b>	Yes
<b>In the Box</b>	PZD2410 24" LCD Monitor, Power Cord, DP Cable, USB Type-C Cable, User's Guide
<b>UPC</b>	8 10689 00988 7
<b>Recommended Daisy Chain Monitor</b>	PXN2410 (998-2944-00)

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 5/19/2022*

*© Copyright 2022 Planar Systems, Inc. All rights reserved*