



# PLL2450MW

## 24" LCD Monitor

The cost-effective Planar® PLL2450MW 24" Full HD LCD desktop monitor features wide viewing angles, integrated TrueMedia™ speakers and VGA and HDMI video inputs. With its small footprint, the Planar PLL2450MW can be mounted on a multi-monitor stand for home, office or healthcare applications.



SPECIFICATION	DETAIL
Product Name	PLL2450MW
Planar Part Number	997-9045-00
Viewable Size	23.6" diagonal (20.52" horizontal x 11.54" vertical)
Aspect Ratio	16:9
Contrast Ratio (typ)	3000:1
Viewing Angle (typ)	178° Horizontal and 178° Vertical (Specified at CR>10:1)
Response Time (typ)	12.5 ms (GTG)
Brightness (Typical)	250 cd/m <sup>2</sup>
Display Type	Edge-Lit LED LCD
Display Resolution	1920 x 1080, full HD
Tilt Range	-5° to +20°
Palette	16.7 million colors
Pixel Pitch	0.2715 mm
Refresh Rate	55-76Hz (60Hz recommended)
Dimensions (W x H x D)	21.6" x 16.0" x 6.7" (547.6 mm x 405.5 mm x 170.4 mm)
Dimensions without Stand	21.6" x 16.0" x 1.6" (547.6 mm x 405.5 mm x 40.9 mm)
Panel Depth	1.6" (40.9 mm)
Display Weight	6.9 lb (3.12 kg), 6.4 lb (2.87 kg) without base & stand
Shipping weight	8.5 lb (3.85 kg)
Video Inputs	HDMI, VGA
HDCP	Yes

<b>External Connections</b>	HDMI 19-pin, VGA 15-pin, 3.5 mm audio in, 3.5 mm headphone out
<b>Audio Output</b>	Integrated TrueMedia™ speakers, 1W/channel
<b>Compatibility</b>	PC and Mac® (adapter may be required for Mac)
<b>Power Supply</b>	Internal
<b>Power Consumption (max)</b>	18.5 Watts typical (<0.5W standby)
<b>Power Requirements</b>	AC 100/240 VAC
<b>Operating Temperature</b>	5° to +40°C (41° to 104°F)
<b>Humidity</b>	10 - 90% RH (non-condensing)
<b>Mount</b>	Built-in 100 mm VESA, back
<b>Product Approvals</b>	FCC-B, CE, UL/cUL, RoHS
<b>Recommended Usage</b>	Up to 16 hours per day
<b>Service and Support</b>	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only). Please see warranty document for more details and for replacement procedures outside the US.
<b>Options / Features</b>	Wide viewing angles, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot
<b>Blue Light Reduction</b>	Yes
<b>Flicker Free</b>	Yes
<b>In the Box</b>	PLL2450MW 24" LED LCD Monitor, C5 Connector Power Cord, HDMI Cable, User's Guide
<b>UPC</b>	8 10689 00410 3

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 3/8/2021*

*© Copyright 2021 Planar Systems, Inc. All rights reserved*