



Planar PXN2480MW

24" Desktop Monitor

The Planar® PXN2480MW is a 24" widescreen IPS LED backlit LCD desktop monitor that features a nearly borderless design, wide viewing angle, DisplayPort and HDMI inputs, external power supply and is available in black. The Planar PXN2480MW fits seamlessly into home, office, healthcare and digital signage environments.



SPECIFICATION	DETAIL
Product Name	PXN2480MW
Planar Part Number	998-0410-00
Viewable Size	23.8" diagonal (20.75" horizontal x 11.67" vertical)
Aspect Ratio	16:9
Contrast Ratio (typ)	1000:1
Viewing Angle (typ)	178° Horizontal and 178° Vertical (Specified at CR>10:1)
Response Time (typ)	7 ms (GTG)
Brightness (Typical)	250 cd/m ²
Display Type	IPS LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	1920 x 1080, full HD
Tilt Range	-5° to +20°
Palette	16.7 million colors
Pixel Pitch	0.2745 mm
Refresh Rate	55~76 Hz (60 Hz recommended)
Dimensions (W x H x D)	21.30" x 16.7" x 4.7" (541 mm x 424.8 mm x 119.1 mm)
Dimensions without Stand	21.30" x 12.75" x 1.2" (540.4 mm x 323.8 mm x 30.5 mm)
Panel Depth	1.2" (30.5 mm)
Display Weight	7.8 lb (3.5 kg); Weight without stand: 6.4 lb (2.9 kg)
Shipping weight	11 lb (5.0 kg)
Video Inputs	HDMI, DisplayPort, VGA
HDCP	Yes
Audio Output	1W x 2, headphone out
External Connections	HDMI 19-pin, DisplayPort 20-pin, VGA 15-pin, 3.5 mm audio in.

Compatibility	PC and Mac® (adapter may be required for Mac)
Power Supply	External (DC power)
Power Consumption (max)	18.5 Watt Typical (<0.5 Watt standby)
Power Requirements	AC 100/240 VAC
Operating Temperature	5° to +40°C (41° to 104°F)
Humidity	10 - 90% RH (non-condensing)
Mount	Built-in 100 mm VESA, back
Product Approvals	FCC-B, UL/cUL, RoHS
Recommended Usage	Up to 16 hours per day
Service and Support	3-Year Customer First™ Warranty featuring FREE 2-Day Advance Replacement (US only). Please see warranty document for more details and for replacement procedures outside the US.
Options / Features	IPS Wide color consistent viewing angle, Nearly Borderless bezel, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot
Blue Light Reduction	Yes
Flicker Free	Yes
In the Box	PXN2480MW 23.8" LED LCD Monitor, 12V DC AC Adaptor, Power Cord, VGA Cable, DisplayPort Cable, Audio Cable, User's Guide
UPC	8 10689 00575 9

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 3/9/2021

© Copyright 2021 Planar Systems, Inc. All rights reserved