

Planar PZN3815Q

38" Curved Docking Monitor

The Planar® PZN3815Q is a 38-inch ultrawide curved docking monitor featuring WQHD+ resolution (3840x1600) with a 2300R curvature. Its 10-bit IPS panel delivers 1.07 billion colors and covers 98% of the DCI-P3 color gamut, ensuring vibrant and precise visuals. With USB Type-C connectivity and an integrated docking station, it allows seamless connection to PCs or laptops. Additional features include built-in speakers, LED light ring as well as a KVM switch for sharing a keyboard, mouse and display between two PCs. The USB-C cable supports audio, video and data transfer while providing up to 96 watts of power. Designed with an ergonomic stand, this monitor is ideal for education, home, office, and healthcare environments.



SPECIFICATION	DETAIL
Product Name	PZN3815Q
Planar Part Number	998-4078-00
Viewable Size	37.5" diagonal (34.63" x 14.43")
Aspect Ratio	21:9 (Ultrawide)
Curvature	2300R
Contrast Ratio (typ)	2000:1
Viewing Angle (typ)	178° Horizontal and Vertical
Response Time (typ)	6 ms (GTG)
Brightness (Typical)	300 cd/m ²
Display Type	IPS LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	3840 x 1600 WQHD+
Tilt Range	-5° to +15°
Palette	1.07 Billion colors

Color Gamut	98% DCI-P3
Pixel Pitch	0.22908 mm
Refresh Rate	48-75Hz (75Hz recommended)
Dimensions (W x H x D)	35.63" x 16.6" x 9.4" (879.7 mm x 421.3 mm x 237.8mm)
Dimensions without Stand	35.63" x 16.6" x 4.2" (879.7mm x 421.3mm x 105.9mm)
Panel Depth	4.2" (105.9 mm)
Display Weight	20.7 lb/9.4 kg (14.6 lb/ 6.6kg without stand)
Shipping weight	29.8 lb (13.5 kg)
Video Inputs	USB Type C (DisplayPort Alt Mode), DisplayPort, HDMI® x 2
HDCP	Yes
Audio Output	Integrated 2W/channel stereo speakers, headphone jack
External Connections	USB Type C 24-pin, HDMI 19-pin \times 2, DisplayPort 20-pin, 3.5mm headphone out, USB (Type B) \times 1, USB (Type A) \times 2
USB	USB-C x 1 (Upstream) (5Gbps), USB3.2 Gen1 x 2 (Downstream)
USB C Power Delivery	USB C (Up to 96W) (5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/4.8A)
Compatibility	PC and Mac® (adapter may be required for Mac)
Power Supply	Internal
Power Consumption (max)	38W typical (<0.5W standby), 125W (Max)
Power Requirements	AC 100/240 VAC
Operating Temperature	0° to +40°C (32° to 104°F)
Humidity	10 - 85% RH (non-condensing)
Mount	Built-in 100 mm VESA, back (VESA plate adapter included)
Product Approvals	cTUVus, CE , FCC-B, RoHS
Recommended Usage	Up to 16 hours per day
Service and Support	3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for

	replacement procedures outside the US.
Options / Features	IPS panel, PIP (Picture in Picture)/ PBPB (Picture by Picture), KVM switch, Discreet branding, Height adjustment: 5.1" (130cmm), Swivel range 60° (30° left, 30° right), LED light ring, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot
Blue Light Reduction	Yes
Flicker Free	Yes
In the Box	PZN3815Q 38" LCD Monitor, Adaptor, Power Cord, HDMI & DP Cable, USB Type-C Cable, USB A to B Cable, VESA Plate adapter, User's Guide
UPC	8 10069 81175 8
HDMI®	Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 6/20/2025

© Copyright 2025 Planar Systems, Inc. All rights reserved