



# Planar URP49-T

## 4K LCD Touch Display

The Planar® URP49-T is a 49" 4K (3840 x 2160) LCD touch screen display with enterprise-level features ideal for collaborative and interactive environments. It features protective glass and pin-point accurate projected capacitive touch that supports up to 50 simultaneous touch points. The 24x7 solution lets users view up to four sources simultaneously and enables administrators to receive remote monitoring email alerts if a designated events occur. The Planar URP49-T is ENERGY STAR® Certified.



SPECIFICATION	DETAIL
Product Name	URP49-T
Planar Part Number	998-2888-00
Protective Glass	3mm with AG+AF coating
Touch Technology	Projected Capacitive
OS Compatibility	Windows 7, 8, 10, 11, Mac OSX and Linux
Display Resolution	Ultra HD (3840 x 2160)
Screen Size	49 in. (diagonal)
Aspect Ratio	16:9
Display Technology	Edge-lit LED LCD
Display Active Area	42.3" x 23.8" (1073.8mm x 604.0mm)
Viewing Angle (typ)	178°
Backlight	LED
Backlight life (1/2 brightness)	30,000 hrs (min)
Brightness (w/protective glass)	450 nits
Response Time (typ)	8 ms
Frame Rate	60Hz
Contrast Ratio (typ)	1100:1
Pixel Pitch	0.2796 mm
Color Gamut	72% NTSC
Display Color	>1 billion colors. Full 10 bit data path

<b>External Connections</b>	DisplayPort 1.2 x 2, HDMI 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2, VGA x 1
<b>Modes</b>	3840x2160 @ 24/25/30/50/60Hz; 1080p @ 24/25/30/50/60Hz; 1080i @ 50/60 Hz; 480p, 576p, 720p @ 50/60 Hz
<b>Display Control</b>	IR, RS-232, LAN, HDMI-CEC, Keypad
<b>Cabinet Dimensions (W x H x D)</b>	44.4" x 25.9" x 2.7" (1127.2mm x 657.4mm x 69.8mm)
<b>Cabinet Dimensions with Handles (W x H x D)</b>	44.4" x 25.9" x 3.1" (1127.2mm x 657.4mm x 78.8mm)
<b>Orientation</b>	Landscape/Portrait
<b>Bezel Width</b>	0.1" (1.5mm)
<b>Display Edge to Active Area</b>	1.1" (26.7mm)
<b>Weight</b>	63.1 lbs (28.6 kg)
<b>Audio Input</b>	PC Line In
<b>Audio Output</b>	PC Line Out, S/PDIF
<b>Speakers</b>	10W x 2 built-in
<b>Enclosure</b>	Metal, Industrial
<b>Mounting</b>	VESA: 300mm x 300mm
<b>Fanless</b>	Yes
<b>Line Voltage</b>	100-240V; 50/60Hz
<b>Power Consumption (typ)</b>	79W (standby: <0.5W)
<b>AC Output Current (max)</b>	3A
<b>Operating Temperature</b>	0° to +40°C (32° to 104°F) up to 3000m
<b>Humidity</b>	20 - 85% RH (non-condensing)
<b>Options / Features</b>	On/Off scheduling, Presets
<b>Auto Brightness Control</b>	Ambient light sensor
<b>Multi-Source Views</b>	PiP, Dual, Quad
<b>Approvals</b>	FCC Class A, CE, cTUVus, RoHS
<b>ENERGY STAR Certified</b>	Yes
<b>TAA Compliance</b>	Yes
<b>Security</b>	No WiFi, no Android O/S, signed and encrypted firmware, tamper-resistant stickers, ability to disable communication interfaces, Secure Shell (SSH) protocol
<b>Warranty</b>	3 years Advance Exchange
<b>Recommended Usage</b>	Up to 24x7
<b>In the Box</b>	URP49-T display, power cord, HDMI cable, IR cable, USB A to B cable, remote control, cable clips, passive stylus, TouchMark license key (one time download), and Quick Start Guide
<b>UPC</b>	8 10689 00992 4

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 12/8/2022*

*© Copyright 2022 Planar Systems, Inc. All rights reserved*