



Clarity Matrix G3

LX46U-3D

3D LCD Video Wall

The Clarity® Matrix® G3 LX46U-3D Video Wall is designed for professional visualization environments seeking a flicker-free stereoscopic 3D display wall. The Clarity Matrix G3 LX46U-3D adds a new dimension to the Clarity Matrix G3 LCD Video Wall family, utilizing its unique design with an ultra-shallow install depth of only 3.6"/93mm, integrated Planar® EasyAxis™ Mounting System, and off-board electronics to create exceptional 3D visualization. Clarity Matrix G3 LX46U-3D features a tiled bezel width of just 3.7mm and offers 1920x1080 resolution.



SPECIFICATION	DETAIL
Technology	Commercial-grade direct view LCD
Diagonal	46in 1168mm
Aspect Ratio	16:9
Native Resolution Panels	1920 x 1080
Tiled Bezel Width	0.15" (3.7 mm)
Brightness (typ)	500 nits (2D)
Response Time (typ)	8 ms
Contrast ratio (full field)	4000:1
Full viewing angle	178°
Backlight life (1/2 brightness)	50,000 Hrs
Mounted Depth	3.6" wall to front of screen EasyAxis Mounting
Acoustic Noise	Fanless operation
Heat load	563 BTU per hour
Operating Temperature/Humidity (degrees F/C, relative humidity)	5° to 40° C / 20-90% RH 41° to 104° F / 20-90% RH
Backlight control	Individual and wall control
Backlight sensing and reporting	At display level
Display module position sensing	Auto-sensing integrated

Power Consumption (typ)	106 watts /Display
Power supply voltage	100-240V AC ± 10%, 50-60 Hz
Power Status	Diagnostics LEDs, health monitoring and alerts
Safety regulations	Complies with EN60950, FCC Class A, CISPR22/85, CE, EU RoHS
Data Inputs	4 HDMI Inputs, 1 DisplayPort Input
Control	IR Remote, RS232, Ethernet
Per Panel Dimensions (Including Mount)	40.2 x 22.7 x 3.6in 1022 x 577 x 91mm
Per Panel Weight (Including Mount)	41lb 18.6kg
Shipping weight	142 lb 64.4 kg

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 12/10/2018

© Copyright 2018 Planar Systems, Inc. All rights reserved