

## Planar CarbonLight CLI VX2.6 B

LED Video Wall

Planar® CarbonLight<sup>TM</sup> CLI VX2.6 B is a carbon fiber-framed indoor LED video wall display with adaptable design suitable for hanging, wall mounting and free-standing installations. Its narrow 2.6mm pixel pitch, high frame rate, genlock compatibility and wide color gamut make it ideal for oncamera virtual production and extended reality.

Planar CarbonLight CLI VX2.6 B is specifically designed to maximize the capabilities of Brompton Technology® video controllers.



| SPECIFICATION                      | DETAIL                                    |
|------------------------------------|---|
| Planar Model                       | CLI VX2.6 B                               |
| Pixel Pitch                        | 2.60                                      |
| Cabinet Resolution                 | 192 x 192                                 |
| Pixel Density                      | 147,456/m2   13,692/ft2                   |
| Cabinet Size (W x H x D)           | 500 x 500 x 63mm   19.69 x 19.69 x 2.48in |
| Cabinet Diagonal                   | 707.1mm   27.8in                          |
| Cabinet Area                       | 0.25m2   2.69ft2                          |
| Modules/Cabinet (W x H)            | 2 x 4                                     |
| Module Size                        | 250x125mm   9.84x4.92in                   |
| Power Consumption, Maximum (watts) | 225/Cabinet   900/m2                      |
| Line Voltage                       | 100-240V AC, 50/60Hz                      |
| Cabinet Weight (per display)       | 4.3kg   9.48lbs                           |
| Cabinet Weight (per m²)            | 17.2kg   37.92lbs                         |

| Brightness  | 1500  |
|---|---|
| Contrast Ratio  | 4000:1  |
| Scan Ratio  | 1:16  |
| LED Refresh Rate  | 3840Hz  |
| Frame Rate (Processor dependent)                                | 24~144Hz  |
| Color Temperature, Adjustable (k)                               | 3,000 - 9,000   |
| Viewing Angle, Horizontal                                       | 140°  |
| Viewing Angle, Vertical   | 140°  |
| Installation and Service Access                                 | Front (modules), Rear   |
| Grey Scale Processing   | 16bit   |
| Operating Temperature/Humidity (degrees F/C, relative humidity) | -20° to 40° C   -4° to 104° F<br>10-80%   |
| Storage Temperature/Humidity (degrees F/C, relative humidity)   | -35° to 60° C   -31° to 140° F<br>10-80%  |
| LED Lifetime (Half Brightness)                                  | 100,000 hrs   |
| Power Supply  | Single  |
| Cooling   | Fan: programmable   |
| Acoustic Noise  | 34db  |
| Active Cooling  | Yes   |
| Warranty  | 3 years; 24-hour customer service   |
| HDMI®   | Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. |

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 6/20/2025

© Copyright 2025 Planar Systems, Inc. All rights reserved