



# Planar CarbonLight CLI2.6S

## Indoor LED Video Wall

The next-generation Planar® CarbonLight™ CLI Series line of indoor LED video wall displays are sleek, lightweight and built for durability with advanced carbon fiber frames. Designed for versatility, these displays support hanging, free-standing, and wall-mounted installations. Available in flexible cabinet sizes of 500x500mm and 500x1000mm, their quick set-up makes them perfect for a wide range of fixed and temporary applications.



SPECIFICATION	DETAIL
Product Name	CLI2.6S
Video Controller	ColorLight
Pixel Pitch	2.60
Pixel Density	147,456 px/m <sup>2</sup>
Cabinet Resolution	192 x 192
Cabinet Size (W x H x D)	500 x 500 x 67 mm
Cabinet Weight (per display)	4.3 kg
Modules per Cabinet (W x H)	2 x 2
Module Size (W x H)	250 x 250 mm
Brightness Max (cd / sq m)	1,500 cd/m <sup>2</sup>
Color Temperature (Calibrated)	6500 K
Contrast Ratio	4000:1
Viewing Angle, Horizontal	140°
Viewing Angle, Vertical	140°
Grey Scale	16 bit

LED Refresh Rate	7,680 Hz
Frame Rate	50 - 60 Hz
Power Supply	Single
Line Voltage	100-240 V AC, 50/60 Hz
Power Consumption, Maximum	800 W/m2
Power Consumption, Typical	270 W/m2
Operating Temperature/Humidity (degrees F/C, relative humidity)	-20° to 40° C (-4° to 104° F)   10% - 90%
Storage Temperature/Humidity (degrees F/C, relative humidity)	-35° to 60° C (-31° to 140° F)   10% - 85%
LED Lifetime, Typical	100,000 hrs
Cabinet Material	Carbon Fiber
Installation	Hanging   Standing
Service Access	Front   Rear
Weight Bearing Capacity (per Cabinet)	FADock/Lock: 1,000 kg (2,205 lbs)   AMDock/Lock: 500 kg (1102 lbs)
Regulation Compliance	FCC, cTUVus, CE, CB, RoHS
Protection	IP40

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 6/20/2025*

*© Copyright 2025 Planar Systems, Inc. All rights reserved*