



# Planar VSI2.5

## Indoor Rental & Staging LED Video Wall Display

The Planar® VSI2.5 is an indoor rental and staging LED video wall display that takes event viewing experiences to the next level. With high brightness and contrast ratio, it delivers crisp images that audiences love. Magnetically-attachable, lightweight tiles with ratcheting quick-locks enable fast, single-person installation and disassembly. Designed with corner protection and an anti-collision edge to withstand frequent assembly and teardown, it is the LED display stagers demand.



SPECIFICATION	DETAIL
Part Number	VSI2.5
Pixel Pitch	2.5mm
Cabinet Resolution	200x200
Pixel Density	160000/sq m   14864/sq ft
LED Cabinet Size (W x H x D)	500 x 500 x 77mm   19.69 x 19.69 x 3.03in
Cabinet Diagonal	707mm   27.8in
Cabinet Area	0.25m <sup>2</sup>   2.69 ft <sup>2</sup>
Modules/Cabinet (W x H)	2x2
Module Size	250 x 250 mm   9.84 x 9.84 in
Power Consumption, Maximum (watts)	155/Cabinet   620/sq m
Line Voltage	100~240V AC, 50/60Hz
Cabinet Weight (per display)	7kg   15.43lb
Cabinet Weight (per m <sup>2</sup> )	28kg   61.73lb
Brightness	1000
Contrast Ratio	4000:1
LED Refresh Rate	3840Hz
Color Temperature, Adjustable (k)	3000 - 10000

<b>Viewing Angle, Horizontal</b>	140°
<b>Viewing Angle, Vertical</b>	140°
<b>Service Access</b>	Front (module) / Rear
<b>LED Lifetime: Typical</b>	75000 hr
<b>Environmental</b>	Indoor
<b>Protection</b>	IP40
<b>Operating Temperature/Humidity (degrees F/C, relative humidity)</b>	-20° to 40° C   4° to 104° F
<b>Storage Temperature/Humidity (degrees F/C, relative humidity)</b>	-35° to 60° C   -31° to 140° F
<b>Installation, Service</b>	Hanging, Stacking
<b>Controller</b>	S6F Controller

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 5/30/2023*

*© Copyright 2023 Planar Systems, Inc. All rights reserved*