

The Leyard® VersaLight™ VLI2.5 is an indoor LED video wall display designed for digital signage. With a self-contained modular structure that can be easily modified to fit a wide range of installation strategies, Leyard VersaLight Series can turn even the most challenging environments into dramatic, inspiring video walls with stunning image quality and ultra-reliable performance.



SPECIFICATION	DETAIL
<b>Product Name</b>	VLI2.5
<b>Part Number</b>	VLI2.5
<b>Pixel Pitch</b>	2.5mm
<b>LED Type</b>	Commercial grade 3-in-1 SMD
<b>Cabinet Resolution</b>	96 x 192
<b>LEDs per Cabinet</b>	18,432
<b>Pixel Density</b>	160000 / m <sup>2</sup>   2123 / ft <sup>2</sup>
<b>Cabinet Size (W x H x D)</b>	240 x 480 x 77.7mm   9.45 x 18.9 x 3.06in
<b>Mounted Depth</b>	93.4 mm / 3.7"
<b>LED Cabinet Diagonal</b>	537mm   21.14in
<b>Cabinet Area</b>	0.1152 m <sup>2</sup>   1.24 ft <sup>2</sup>
<b>Brightness Max (cd / sq m)</b>	1000
<b>Power Consumption, Maximum (watts)</b>	75 watts / cabinet   650 watts / m <sup>2</sup>
<b>Power Consumption, Typical (watts)</b>	25 watts / cabinet   217 watts / m <sup>2</sup>
<b>Line Voltage</b>	100-240V AC, 50/60Hz auto ranging

<b>Cabinet Weight (per display)</b>	2.8 kg   6.1 lb
<b>Cabinet Weight (per m<sup>2</sup>)</b>	24.3 kg   53.6 lb
<b>Cabinet Weight with mount</b>	3.93 kg   8.7 lb
<b>Cabinet Weight with mount (per m<sup>2</sup>)</b>	34.1 kg / m <sup>2</sup>   75.2 lb / m <sup>2</sup>
<b>2x2 Mount Weight</b>	4.5 kg   10 lb
<b>2x2 Mount Weight (per cabinet)</b>	1.13 kg   2.5 lb
<b>2x2 Mount Weight (per sq m)</b>	9.8 kg / m <sup>2</sup>   21.6 lb / m <sup>2</sup>
<b>2x2 Cabinet Weight with mount</b>	15.7 kg   34.6 lb
<b>Contrast Ratio</b>	>5000:1
<b>Brightness Uniformity</b>	>97%
<b>Color Uniformity</b>	>97%
<b>Color Gamut</b>	100% NTSC
<b>LED Refresh Rate</b>	2000Hz
<b>Color Temperature, Adjustable (k)</b>	3000 - 10000
<b>Viewing Angle, Horizontal</b>	160°
<b>Viewing Angle, Vertical</b>	140°
<b>Video Inputs</b>	1 x HDMI in, 6 x Cat6 / RJ45 output
<b>Video Input Resolution Maximum</b>	Any resolution totaling up to 2.3M pixels. Max width: 4096, max height: 2560
<b>Frame Rate</b>	50, 60Hz
<b>Control Input Type</b>	USB, Ethernet
<b>Gray Scale Processing</b>	18-bit
<b>Installation and Service Access</b>	Front
<b>Wall Mount</b>	Wall-mountable frame included
<b>LED Lifetime: Typical</b>	> 80000 hrs
<b>Environment</b>	Indoor
<b>Power Supply</b>	Single onboard power supply per module
<b>Protection</b>	IP30
<b>Acoustic Noise</b>	<35 dB
<b>Maximum Cabinets Per 120V 15A Circuit</b>	20
<b>Maximum Cabinets Per 240V 15A Circuit</b>	43

<b>Operating Temperature/Humidity (degrees F/C) 10-80% relative humidity, non-condensing</b>	-10° to 40° C   14° to 104° F
<b>Maximum Cabinets Per 208V 15A Circuit</b>	36
<b>Storage Temperature/Humidity (degrees F/C) 10-85% relative humidity, non-condensing</b>	-20° to 60° C   -4° to 140° F
<b>Regulatory Compliance</b>	NRTL, FCC Class A, CE Class A, WEEE, EN60950 and CISPR 22/2010 certification

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 5/24/2019*

*© Copyright 2019 Planar Systems, Inc. All rights reserved*