

The Leyard® VersaLight™ VLI2.5 is an indoor LED video wall display designed for digital signage. With a self-contained modular structure that can be easily modified to fit a wide range of installation strategies, Leyard VersaLight Series can turn even the most challenging environments into dramatic, inspiring video walls with stunning image quality and ultra-reliable performance.



SPECIFICATION	DETAIL
Product Name	VLI2.5
Part Number	VLI2.5
Pixel Pitch	2.5mm
LED Type	Commercial grade 3-in-1 SMD
Cabinet Resolution	96 x 192
LEDs per Cabinet	18,432
Pixel Density	160000 / m ² 2123 / ft ²
Cabinet Size (W x H x D)	240 x 480 x 77.7mm 9.45 x 18.9 x 3.06in
Mounted Depth	93.4 mm / 3.7"
LED Cabinet Diagonal	537mm 21.14in
Cabinet Area	0.1152 m ² 1.24 ft ²
Brightness Max (cd / sq m)	1000
Power Consumption, Maximum (watts)	75 watts / cabinet 650 watts / m ²
Power Consumption, Typical (watts)	25 watts / cabinet 217 watts / m ²
Line Voltage	100-240V AC, 50/60Hz auto ranging

Cabinet Weight (per display)	2.8 kg 6.1 lb
Cabinet Weight (per m²)	24.3 kg 53.6 lb
Cabinet Weight with mount	3.93 kg 8.7 lb
Cabinet Weight with mount (per m²)	34.1 kg / m ² 75.2 lb / m ²
2x2 Mount Weight	4.5 kg 10 lb
2x2 Mount Weight (per cabinet)	1.13 kg 2.5 lb
2x2 Mount Weight (per sq m)	9.8 kg / m ² 21.6 lb / m ²
2x2 Cabinet Weight with mount	15.7 kg 34.6 lb
Contrast Ratio	>5000:1
Brightness Uniformity	>97%
Color Uniformity	>97%
Color Gamut	100% NTSC
LED Refresh Rate	2000Hz
Color Temperature, Adjustable (k)	3000 - 10000
Viewing Angle, Horizontal	160°
Viewing Angle, Vertical	140°
Video Inputs	1 x HDMI in, 6 x Cat6 / RJ45 output
Video Input Resolution Maximum	Any resolution totaling up to 2.3M pixels. Max width: 4096, max height: 2560
Frame Rate	50, 60Hz
Control Input Type	USB, Ethernet
Gray Scale Processing	18-bit
Installation and Service Access	Front
Wall Mount	Wall-mountable frame included
LED Lifetime: Typical	> 80000 hrs
Environment	Indoor
Power Supply	Single onboard power supply per module
Protection	IP30
Acoustic Noise	<35 dB
Maximum Cabinets Per 120V 15A Circuit	20
Maximum Cabinets Per 240V 15A Circuit	43

Operating Temperature/Humidity (degrees F/C) 10-80% relative humidity, non-condensing	-10° to 40° C 14° to 104° F
Maximum Cabinets Per 208V 15A Circuit	36
Storage Temperature/Humidity (degrees F/C) 10-85% relative humidity, non-condensing	-20° to 60° C -4° to 140° F
Regulatory Compliance	NRTL, FCC Class A, CE Class A, WEEE, EN60950 and CISPR 22/2010 certification

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 12/10/2018

© Copyright 2018 Planar Systems, Inc. All rights reserved