

eyevis EC-SLIM-60-LHD-WVF-FS

Rear Projection Video Wall

Theeyevis™ SLIM Series is a line of DLP® rear projection video wall displays with the slimmest profile for space-constrained environments. Available in 50", 60" and 70" sizes, the eyevis SLIM Series features Full HD resolution with a depth as small as 432mm (12").



SPECIFICATION	DETAIL
Part Number	998-0860-00
Diagonal	60 inch (ca. 152 cm)
Display Resolution	1920x1080 / Chip: 1080P / 0.65 inch DMD@LVDS
Aspect Ratio	16:9
Brightness	Max: 430 cd/m² ; Typ: 310 cd/m² ; Eco: 185 cd/m²
Brightness Uniformity	95% (SUR25)
Color and Brightness Control	Automatic colour adjustment, internal True-Colour sensor
Contrast Ratio	1000:1 (typ. / static contrast) / up to 10.000:1 (active LED control)
Acoustic Noise	max. 36dB / 30 dB with enclosure at 3 metres distance from screen facing side
Frame Rate	48 to 64 Hz (non-stereo), 120 Hz (active stereo)
Inputs	Signal: 1x DisplayPort 1.2 Communication: RS232 (in and out for daisy chain), 1x LAN
Screen Type	Wide View FEL Screen (WVF)
Viewing Angle	H: 38° / V: 21° (Half Gain Angle)
LED Lifetime	>60,000 hrs under normal environmental conditions / L70B50 manufacturer information) (>100,000 hrs in 'Reduced Power (ECO) Operation Mode')
Screen Size	(WxH) 1328x747 mm, 52.28"x29.41"
Dimensions	(WxHxD) 1328x1270x487 mm, 52.28"x50"x19.17"
Installation and Service Access	Installation on height-adjustable basements with front or rear access; Installation directly wall mounted
Screen gap (typical)	1.5 mm (front access)
Weight	ca. 72 kg, 159 lbs

Power Consumption (Opt./Typ./Eco) - Watts	155W / 130W / 80W
Temperature Range	10-40° C recommended 15 - 25 °C for Seamless Screens 18 - 25 °C Storage: 0 - 50 °C
Humidity Range	0% - 80 % not condensing